



**NOTES:**

1. RoHS COMPLIANT
2. SUITABLE FOR WAVE SOLDERING
3. METAL SHELLS: COPPER ALLOY; min. 315µm TIN over 40-80µm NICKEL
4. INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0, BLACK
5. CONTACTS: COPPER ALLOY  
PLATING: 8µm HARD GOLD over min. 50µm NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 26
6. THREADED INSERT: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
7. COLLAR: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
8. CAPACITANCE: 1300pF ± 20%
9. DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
10. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
11. CONNECTOR IS PART MARKED: FDCRXSLAG04S132X CONEC ABC

Directive 2002/95/EC  
"RoHS"  
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH			
DO NOT ALTER CAD DRAWING BY HAND			
rev.	description	date	name

tolerance		dim. in mm	
date	name		
drawn 12.11.07	Lehmenkühler		
appd. 12.11.07	Mickenbecker		
norm			
d-old			

scale: 2:1 (5:1)	
material: SEE NOTES	
title: <b>D-SUB FILTER FEMALE</b> 25pos. SOLDER CUP with threaded insert	
dwg no: Inventor 10	DIN-A3
24K1A1054	
part no: <b>FDCRXSLAG04S132X</b>	
sh: 1	

