9 INCHES LENGTH





Connector A 132195 SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-142 Continuity/Hi-Pot Connector B 142203 SMB Plug Right Angle Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector A			Cable		Connector B	
Part #:	132195	Part #:	RG-142	Part #:	142203	
Description:	SMA Plug RG142 50O	Description:	RG-142 - ST 0.195	Description:	SMB PLUG RG55 RG142 RG223 500	
Type:	SMA	Dielectric:	ST	Type:	SMB	
Gender:	Plug	Shielding:	Braid	Gender:	Plug	
Body Type:	Straight	Diameter:	0.195	Body Type:	Right Angle	
Contact Type:	Solder	Impedance:	50 Ohm	Contact Type:	Solder	
Polarity:	Standard	Sheathing:	None	Polarity:	Standard	
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm	
Mounting:	Cable	Length:	9 Inches	Mounting:	Cable	
Body Material:	Brass			Body Material:	Brass	
Body Finish:	Gold			Body Finish:	Gold	
IP Rating:	None			IP Rating:	None	
Contact Material:	Brass			Contact Material:	Beryllium Copper	
Contact Finish:	Gold			Contact Finish:	Gold	
Max. Freq.:	12.4 GHz			Max. Freq.:	4 GHz	
Booting:	SMA Plug Straight			Booting:	SMB Plug Right Angle	
				Clocking:	0°	



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-ST-PL/SMB-RA-PL G142 9I

Part No:

Q-3F03V000H009I

UNLESS SPECIFIED

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES