

C2M0025120D

Silicon Carbide Power MOSFET C2MTM MOSFET Technology

N-Channel Enhancement Mode

Features

- High Blocking Voltage with Low On-Resistance
- High Speed Switching with Low Capacitances
- Easy to Parallel and Simple to Drive
- Avalanche Ruggedness
- Resistant to Latch-Up
- Halogen Free, RoHS Compliant

Benefits

- Higher System Efficiency
- Reduced Cooling Requirements
- Increased Power Density
- Increased System Switching Frequency

Applications


- Solar Inverters
- Switch Mode Power Supplies
- High Voltage DC/DC converters
- Battery Chargers
- Motor Drive
- Pulsed Power Applications

V_{DS}	1200 V
$I_D @ 25^\circ\text{C}$	63 A
$R_{DS(on)}$	25 mΩ

Package



TO-247-3



Part Number	Package	Marking
C2M0025120D	TO-247-3	C2M0025120

Maximum Ratings ($T_c = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Value	Unit	Test Conditions	Note
V_{DSmax}	Drain - Source Voltage	1200	V	$V_{GS} = 0 \text{ V}, I_D = 100 \mu\text{A}$	
V_{GSmax}	Gate - Source Voltage	-10/+25	V	Absolute maximum values	
V_{GSop}	Gate - Source Voltage	-5/+20	V	Recommended operational values	
I_D	Continuous Drain Current	63	A	$V_{GS} = 20 \text{ V}, T_c = 25^\circ\text{C}$	Fig. 19 Note 1
		39		$V_{GS} = 20 \text{ V}, T_c = 100^\circ\text{C}$	
$I_{D(pulse)}$	Pulsed Drain Current	250	A	Pulse width t_p limited by T_{jmax}	Fig. 22
P_D	Power Dissipation	378	W	$T_c = 25^\circ\text{C}, T_j = 150^\circ\text{C}$	Fig. 20
T_J, T_{stg}	Operating Junction and Storage Temperature	-55 to +150	°C		
T_L	Solder Temperature	260	°C	1.6mm (0.063") from case for 10s	
M_d	Mounting Torque	1 8.8	Nm lbf-in	M3 or 6-32 screw	

Note (1): Die limits are 90A (25°C) and 60A (100°C)



Electrical Characteristics ($T_c = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions	Note
$V_{(\text{BR})\text{DSS}}$	Drain-Source Breakdown Voltage	1200			V	$V_{GS} = 0 \text{ V}, I_D = 100 \mu\text{A}$	
$V_{GS(\text{th})}$	Gate Threshold Voltage	2.0	2.6	4	V	$V_{DS} = V_{GS}, I_D = 15 \text{ mA}$	Fig. 11
			2.3		V	$V_{DS} = V_{GS}, I_D = 15 \text{ mA}, T_J = 150^\circ\text{C}$	
I_{DSS}	Zero Gate Voltage Drain Current		2	100	μA	$V_{DS} = 1200 \text{ V}, V_{GS} = 0 \text{ V}$	
I_{GSS}	Gate-Source Leakage Current			250	nA	$V_{GS} = 20 \text{ V}, V_{DS} = 0 \text{ V}$	
$R_{DS(\text{on})}$	Drain-Source On-State Resistance		25	34	$\text{m}\Omega$	$V_{GS} = 20 \text{ V}, I_D = 50 \text{ A}$	Fig. 4,5,6
			41			$V_{GS} = 20 \text{ V}, I_D = 50 \text{ A}, T_J = 150^\circ\text{C}$	
g_{fs}	Transconductance		24.6		S	$V_{DS} = 20 \text{ V}, I_{DS} = 50 \text{ A}$	Fig. 7
			24			$V_{DS} = 20 \text{ V}, I_{DS} = 50 \text{ A}, T_J = 150^\circ\text{C}$	
C_{iss}	Input Capacitance		3140		pF	$V_{GS} = 0 \text{ V}$	Fig. 17,18
C_{oss}	Output Capacitance		224			$V_{DS} = 1000 \text{ V}$	
C_{rss}	Reverse Transfer Capacitance		9			$f = 1 \text{ MHz}$	
E_{oss}	C_{oss} Stored Energy		128		μJ	$V_{AC} = 25 \text{ mV}$	Fig 16
E_{ON}	Turn-On Switching Energy (Body Diode)		2.18		mJ	$V_{DS} = 800 \text{ V}, V_{GS} = -5/20 \text{ V}, I_D = 50 \text{ A}, R_{G(\text{ext})} = 2.5 \Omega, L = 99 \mu\text{H}$	Fig. 25
E_{OFF}	Turn Off Switching Energy (Body Diode)		0.68			FWD = Internal Body Diode of MOSFET	
E_{ON}	Turn-On Switching Energy (External SiC Diode)		1.14			$V_{DS} = 800 \text{ V}, V_{GS} = -5/20 \text{ V}, I_D = 50 \text{ A}, R_{G(\text{ext})} = 2.5 \Omega, L = 99 \mu\text{H}$	
E_{OFF}	Turn Off Switching Energy (External SiC Diode)		0.8		mJ	FWD = External SiC Diode	Fig. 25
$t_{d(on)}$	Turn-On Delay Time		15			$V_{DD} = 800 \text{ V}, V_{GS} = -5/20 \text{ V}$	
t_r	Rise Time		58			$I_D = 50 \text{ A}, R_{G(\text{ext})} = 2.5 \Omega, \text{Inductive Load}$	
$t_{d(off)}$	Turn-Off Delay Time		33			Timing relative to V_{DS}	
t_f	Fall Time		17		ns	Per IEC60747-8-4 pg 83	Fig. 27
$R_{G(\text{int})}$	Internal Gate Resistance		1.0			$f = 1 \text{ MHz}, V_{AC} = 25 \text{ mV}, \text{ESR of } C_{iss}$	
Q_{gs}	Gate to Source Charge		46		nC	$V_{DS} = 800 \text{ V}, V_{GS} = -5/20 \text{ V}$	Fig. 12
Q_{gd}	Gate to Drain Charge		71.5			$I_D = 50 \text{ A}$	
Q_g	Total Gate Charge		194			Per IEC60747-8-4 pg 21	



Reverse Diode Characteristics

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions	Note
V_{SD}	Diode Forward Voltage	4.1		V	$V_{GS} = -5\text{ V}$, $I_{SD} = 25\text{ A}$	Fig. 8, 9, 10
		3.5		V	$V_{GS} = -5\text{ V}$, $I_{SD} = 25\text{ A}$, $T_J = 150\text{ }^\circ\text{C}$	
I_S	Continuous Diode Forward Current		63		$V_{GS} = -5\text{ V}$, $T_C = 25\text{ }^\circ\text{C}$	Note 2
$I_{S,pulse}$	Diode Pulse Current		250		$V_{GS} = -5\text{ V}$, Pulse width t_P limited by T_{Jmax}	
t_{rr}	Reverse Recovery Time	33		ns	$V_{GS} = -5\text{ V}$, $I_{SD} = 50\text{ A}$, $T_J = 25\text{ }^\circ\text{C}$ $VR = 800\text{ V}$ $dif/dt = 2180\text{ A}/\mu\text{s}$	Note 2
Q_{rr}	Reverse Recovery Charge	487		nC		
I_{rrm}	Peak Reverse Recovery Current	24		A		
t_{rr}	Reverse Recovery Time	67		ns	$V_{GS} = -5\text{ V}$, $I_{SD} = 50\text{ A}$, $T_J = 25\text{ }^\circ\text{C}$ $VR = 800\text{ V}$ $dif/dt = 1320\text{ A}/\mu\text{s}$	Note 2
Q_{rr}	Reverse Recovery Charge	386		nC		
I_{rrm}	Peak Reverse Recovery Current	15		A		

Note (2): When using SiC Body Diode the maximum recommended $V_{GS} = -5\text{ V}$

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions	Note
$R_{\theta JC}$	Thermal Resistance from Junction to Case	0.24	0.33	°C/W		Fig. 21
$R_{\theta JC}$	Thermal Resistance from Junction to Ambient		40			

Typical Performance




Figure 1. Output Characteristics $T_J = -55^\circ\text{C}$




Figure 2. Output Characteristics $T_J = 25^\circ\text{C}$




Figure 3. Output Characteristics $T_J = 150^\circ\text{C}$




Figure 4. Normalized On-Resistance vs. Temperature




Figure 5. On-Resistance vs. Drain Current
For Various Temperatures




Figure 6. On-Resistance vs. Temperature
For Various Gate Voltage

Typical Performance




Figure 7. Transfer Characteristic For Various Junction Temperatures




Figure 8. Body Diode Characteristic at -55°C




Figure 9. Body Diode Characteristic at 25°C




Figure 10. Body Diode Characteristic at 150°C




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristic

Typical Performance




Figure 13. 3rd Quadrant Characteristic at $-55\text{ }^{\circ}\text{C}$




Figure 14. 3rd Quadrant Characteristic at $25\text{ }^{\circ}\text{C}$




Figure 15. 3rd Quadrant Characteristic at $150\text{ }^{\circ}\text{C}$




Figure 16. Output Capacitor Stored Energy





Figure 17. Capacitances vs. Drain-Source Voltage (0-200 V)



Typical Performance




Figure 19. Continuous Drain Current Derating vs.
Case Temperature




Figure 20. Maximum Power Dissipation Derating vs.
Case Temperature




Figure 21. Transient Thermal Impedance
(Junction - Case)




Figure 22. Safe Operating Area




Figure 23. Clamped Inductive Switching Energy vs.
Drain Current ($V_{DD} = 600V$)




Figure 24. Clamped Inductive Switching Energy vs.
Drain Current ($V_{DD} = 800V$)

Typical Performance




Figure 25. Clamped Inductive Switching Energy vs. $R_{G(\text{ext})}$




Figure 26. Clamped Inductive Switching Energy vs. Temperature




Figure 27. Switching Times vs. $R_{G(\text{ext})}$




Figure 28. Switching Times Definition

Test Circuit Schematic






Figure 29. Clamped Inductive Switching
Waveform Test Circuit

ESD Ratings

ESD Test	Resulting Classification
ESD-HBM	3A (4000V - 8000V)
ESD-CDM	C3 ($\geq 1000\text{V}$)

Package Dimensions

Package TO-247-3




Pinout Information:

- Pin 1 = Gate
- Pin 2, 4 = Drain
- Pin 3 = Source

POS	Inches		Millimeters	
	Min	Max	Min	Max
A	.190	.205	4.83	5.21
A1	.090	.100	2.29	2.54
A2	.075	.085	1.91	2.16
b	.042	.052	1.07	1.33
b1	.075	.095	1.91	2.41
b2	.075	.085	1.91	2.16
b3	.113	.133	2.87	3.38
b4	.113	.123	2.87	3.13
c	.022	.027	0.55	0.68
D	.819	.831	20.80	21.10
D1	.640	.695	16.25	17.65
D2	.037	.049	0.95	1.25
E	.620	.635	15.75	16.13
E1	.516	.557	13.10	14.15
E2	.145	.201	3.68	5.10
E3	.039	.075	1.00	1.90
E4	.487	.529	12.38	13.43
e	.214 BSC		5.44 BSC	
N	3		3	
L	.780	.800	19.81	20.32
L1	.161	.173	4.10	4.40
ØP	.138	.144	3.51	3.65
Q	.216	.236	5.49	6.00
S	.238	.248	6.04	6.30
T	9°	11°	9°	11°
U	9°	11°	9°	11°
V	2°	8°	2°	8°
W	2°	8°	2°	8°

Recommended Solder Pad Layout



TO-247-3



Notes

- **RoHS Compliance**

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Cree representative or from the Product Documentation sections of www.cree.com.

- **REACH Compliance**

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact a Cree representative to insure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

- This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, air traffic control systems.

Related Links

- **C2M PSPICE Models:** <http://wolfspeed.com/power/tools-and-support>
- **SiC MOSFET Isolated Gate Driver reference design:** <http://wolfspeed.com/power/tools-and-support>
- **SiC MOSFET Evaluation Board:** <http://wolfspeed.com/power/tools-and-support>