



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00397	Connector, 4C audio plug, 3.5xL20.7 mm, brass, nickel plated, molding style	1	
2	30-01375	Wire, 3C, BC, 28 AWG, 300V, 80C, 4.3 mm, shielded, PVC, nylon braid	1	
3	24-00346	Overmold, audio plug, Ø7.2xL23.3 mm	1	PVC, black
4	Heat shrink	Heat shrink, black	1	covers end of jacket
5	Heat shrink	Heat shrink, black	1	covers shield



Wiring Diagram	
50-00397	wire color
A	red
B	white
C	green
D	shield

Notes:
Functionally equivalent components may be substituted

Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	8/10/2020	Initial release	JC Digitally signed by JC Date: 2020.08.10 10:48:01 -07'00'	RoHS compliant	
			Verified:	Function test: no open, no short circuit, no intermittent	
			AW Digitally signed by AW Date: 2020.08.10 13:26:05 -07'00'	Description:	Size: Part number:
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Cable, 1830 mm, 3.5 mm 4C 50-00397 audio plug to 5 mm tinned, 28 AWG, 30-01375 wire, nylon braided	A 10-03723
					Scale: 1:1
					Sheet 1 of 1

5

4

3

2

1