Mallory Sonalert Products, Inc.				Part #: JT028-G-CSL		
Sal	es Outline	Drawing		Revision:		D
Specifications:						
Stack Number:	1					
LED Color:	GREEN					
Connection Wires:	Green and Brown					
LED Current Draw:	<50 mA					
	<united co<="" td=""><td></td><td>04.)/40/D0</td><td></td><td></td><td></td></united>		04.)/40/D0			
Rated Voltage:			24 VAC/DC			
Operating Voltage:			20-28 VAC/D0	;	1	
Sound Level Category:	Loud	Loud	Loud			Loud
Mode of Operation:	Continuous	Medium Pulse (5PPS)	Double Pulse (0.	,	Continuous	for 5 sec then 0.1s beep until reset
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to	Black and Gray Wire wire connected to Gray wire			
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max		40mA Max.	
Loudness @ 1m:		•	80-85 dB(A) Ty	p.	•	
Frequency:	2000 ± 500 Hz					
Total Max Current:	<90mA with all LED's and sound unit working					
Operating Temperature:	-25° ~ +60°C					
Lens Color:	Opaque White					
Material:	ABS FR15U					
Mounting Method:	Stainless Steel Pole					
Weight Typical (g):	Starriess Steel Pole 640					
NEMA 12:						
	Approved Please contact factory.					
Options: Dimensions: Inches (mr		cUL Recogn		ctory.		ROHS Compliant
3.7 [94.1] ————————————————————————————————————		5.6 [422.0]———————————————————————————————————	#10 or 5mm screws for mounting 0.95 [24.3]	,5	Ø0.57 [Ø14.6 for wires	.9]
LED OPERATION: CONNECT	CONNECT GRAY AN FOR MEDIUM PULSE FOR DOUBLE PULSE	E, CONNECT GRAY &	POWER FOR CONTIN BLACK TO POWER A BLACK TO POWER A	UOUS SOL ND ORANO ND PURPL	GE WIRE TO E WIRE TO	GREEN/YELLOW WIRE. GREEN/YELLOW WIRE. D GREEN/YELLOW WIRE.
	. SIT SOITI/BELLI, O	C.T. LOT GITAL & DEA	S. TO TOWEITAND	011/11/UL 0		SILLIWILLOW WILL.