


**REVISIONS** ECO **DESCRIPTION APPR** REV DATE BY Α1 RELEASE NEW DRAWING 16/NOV/22 MILO TOMMY



1. MATERIAL:

HOUSING: THERMOPLASTIC; BLACK

SEAL: SILICONE RUBBER

THREADED INSERT: STAINLESS STEEL

2. MODIFICATIONS: SMOOTH RING ADAPTER (SRA); THIN WALL DIA. WIRE SEAL **SEALED PANEL MOUNT** 

## 3. SPECIFICATIONS:

- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
- 3.4 MOISTURE RESISTANCE:

IP68(IM OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION);


IP69K(MATED CONDITION)

- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP06-24-23P\* (\* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6. RECEPTACLE IS SUPPLIED WITH DUST CAP (NOT SHOWN)

## 7 CONTACT SIZE AND WIRE RANGE:


_	<b>-</b>								
	CONTACT	MIN.INSUL	MAX.INSUL	WIRE RANGE					
	SIZE	O.D	O.D	mm²					
	16	2.23mm (.088in)	2.69mm (.106in)	14-20AWG (2.0-0.5mm²)					

RECOMMENDED TORQUE VALUES: 1.9-2.2 N.m.



MOUNTING HOLE

RECOMMENDED PANEL THICKNESS:1.6 TO 4.7MM



QUANTITY	JANTITY   PART NUMBER					
			MA	T	ERI	<b>4</b>
UNLESS OTHERWISE SPECIFIED  1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30   Fractions ±1/64		SIGNATURES		ES	DATE	
		DRAWN:	MILO.DON	G	16/NOV/22	
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	SULLEN.ZHA	NG	17/NOV/22	•
3) Note reference = X		ENGINEER:				
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY.XII	E	18/NOV/22	_
WEIGHT: 62.6g  PROCESS SPECIFICATIONS:		CUSTOMER:				
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL JIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.				
NEXT AGO 1.						

AHDP02-24-23ST-SRA

LS LIST **Amphenol** 

DESCRIPTION

DWG NO:

ITEM

Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036

23POS, RECEPTACLE, SOCKET, SZ24, THIN WIRE SEAL.SRA.PANELMATE AHDP

AHDP02-24-23ST-SRA A1 В SCALE: NONE DURAMATE SHEET 1 OF 1