



- NOTES:
1. MATERIAL: SEE TABLE
  2. FINISHES: SEE TABLE
  3. INCH DMS. ARE SHOWN IN BRACKETS [XXX].
  4. DESIGNED TO MEET UL 1059 CLASS C 600 VOLTS.
  5. SCREWS ARE DRIVEN DOWN FULLY TO CLOSE CAGE CLAMPS.
  6. ASSEMBLY IS ROHS COMPLIANT BY EXEMPTION. COMPONENTS MARKED WITH AN ASTERISK (\*) ARE ROHS COMPLIANT BY EXEMPTION. ALL OTHERS ARE ROHS COMPLIANT.

6	5	REAR TERMINAL	COPPER	TIN PLATE
5	5	FRONT TERMINAL	COPPER	TIN PLATE
4	10	CAGE CLAMP	BRASS *	NICKEL PLATE
3	10	SCREW, M4, #2 POZI-SLOT, BRONZE	BRONZE	TIN PLATED
2	1	COVER	PBT	BLACK
1	1	BODY	PBT	BLACK
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

INITIAL RELEASE	QUALITY SYMBOLS
EC NO: ETC2007-0372	▽=0
DRWN: CLYORK 2007/04/05	▽=0
CHKD: JMACNEIL 2007/04/27	
APPR: JMACNEIL 2007/04/30	
DESCRIPTION	
REV	

GENERAL TOLERANCES (UNLESS SPECIFIED)	
mm	INCH
4 PLACES ± ---	± ---
3 PLACES ± ---	± .005
2 PLACES ± 0.13	± .01
1 PLACE ± 0.3	± ---
ANGULAR ± 2 °	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE	
MM/IN	
DRAWN BY	DATE
C. YORK	2007/04/05
CHECKED BY	DATE
J. MACNEIL	2007/04/05
APPROVED BY	DATE
J. MACNEIL	2007/04/05
MATERIAL NO.	
399190015	

SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
1:1	INCH	
TITLE		
10.16MM [.400] SR BTS		
8 AWG ASSY, 40 AMP, 600V		
W/ CAGES CLOSED		
MATERIAL NO.		
399190015		
DOCUMENT NO.		
SD-39919-012		
SHEET NO.		
1 OF 1		