



TDS Series Touch Screen Digital Storage Oscilloscope

- + Max 200MHz bandwidth, up to 2GS/s realtime sample rate
- + 7.6M record length
- + 50,000 wfms/s waveform capture rate
- + waveform zooming (horizontal / vertical), and saving
- + FFT points (length, and resolution variable)
- + multi-window extension
- + 8 inch 800 x 600 pixels high def LCD
- + multi- communication interface : USB, VGA, and LAN
- + SCPI, and LabVIEW supported

Model	TDS7074	TDS7104	TDS8104	TDS8204
Bandwidth	70MHz	100MHz		200MHz
Channel	4			
Sample Rate	1GS/s		2GS/s	
Waveform Capture Rate	50,000 wfms/s			
Display	8" color LCD			
Input Coupling	DC, AC, and GND			
Input Impedance	1M Ω \pm 2%, in parallel with 15pF \pm 5pF ; 50 Ω \pm 1%			
Probe Attenuation Factor	1X, 10X, 100X, 1000X			
Max Input Voltage	1M Ω input impedance : 400V (PK - PK) (DC + AC, PK - PK) ; 50 Ω input impedance : 5V (PK - PK) (DC + AC, PK - PK)			
Channel Isolation	50Hz : 100 : 1 ; 10MHz : 40 : 1			
Interpolation	sin(x)/x			
Record Length	7.6M			
Horizontal Scale (s/div)	2ns/div - 100s/div, step by 1 - 2 - 5			
Interval (Δ T) Accuracy (full bandwidth)	Single : \pm (1 interval time + 100ppm \times reading + 0.6ns), Average>16 : \pm (1 interval time + 100ppm \times reading + 0.4ns)			
Vertical Resolution (A/D)	8 bits (4 channels simultaneously)			
Vertical Sensitivity	2mV/div - 10V/div (at input)			
Analog Bandwidth	70MHz	100MHz		200MHz
LF Respond (AC, -3dB)	\geq 10Hz (at input, AC coupling, -3dB)			
Rise Time	\leq 5.0ns	\leq 3.5ns		\leq 1.7n
DC Accuracy	\pm 3%			
Trigger Type	Edge, Pulse, Video, and Slope			
Trigger Mode	Auto, Normal, and Single			
Trigger Level Range	\pm 6 division from the screen center			

+ Performance Specifications

+ Application

electronic circuit debugging
education and training

circuit testing

design and manufacture
automobile maintenance and testing

+ Accessories


The accessories subject to final delivery.



Power Cord



CD Rom



Manual



USB



Probe



Probe Adjust



Soft Bag
(optional)