

GRACE INERTIA 2.5 TE Internal #: 1-1903390-2 Rectangular Connector Housings, Wire-to-Wire, 4 Position, .098 in [2.5 mm] Centerline, 1 Row, PBT GF, Plug, Socket, Wire & Cable, GRACE INERTIA 2.5

View on TE.com >

Connectors > Rectangular Connectors > Rectangular Connector Housings > STD Temp Sig GRACE INERTIA Plug



Connector System: Wire-to-Wire Number of Positions: 4

Centerline (Pitch): 2.5 mm [.098 in]

Number of Rows: 1

Housing Material: **PBT GF**

All STD Temp Sig GRACE INERTIA Plug (63)



Features

Product Type Features

Connector System	Wire-to-Wire								
Connector & Housing Type	Plug								
Sealable	No								
Connector & Contact Terminates To	Wire & Cable								
Configuration Features									
Number of Cavities	4								
Number of Positions	4								
Number of Rows	1								
Electrical Characteristics									
Operating Voltage	250 VAC								
Contact Features									
Contact Layout	Inline								

Rectangular Connector Housings, Wire-to-Wire, 4 Position, .098 in [2.5 mm] Centerline, 1 Row, PBT GF, Plug, Socket, Wire & Cable, GRACE INERTIA 2.5



Contact Type	Socket
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Color	Red
Centerline (Pitch)	2.5 mm[.098 in]
Housing Material	PBT GF
Dimensions	
Connector Height	11 mm[.433 in]
Product Width	9.6 mm[.378 in]
Product Length	13.7 mm[.539 in]
Usage Conditions	
Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
Operation/Application	
Circuit Application	Signal
Identification Marking	
Circuit Identification Feature	Without

Industry Standards

Glow Wire Rating	Standard Part - Not Glow Wire							
Packaging Features								
Packaging Quantity	1000							
Packaging Method	Bag							
Product Compliance								
For compliance documentation, visit the product page on TE.com>								
EU RoHS Directive 2011/65/EU	Compliant							
EU ELV Directive 2000/53/EC	Compliant							
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold							
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC							

Rectangular Connector Housings, Wire-to-Wire, 4 Position, .098 in [2.5 mm] Centerline, 1 Row, PBT GF, Plug, Socket, Wire & Cable, GRACE INERTIA 2.5



Halogen Content
Not Low Halogen - contains Br or Cl > 900 ppm.

Adductor of the block of the second secon

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CAT-G7534A-P729 STD Temp Sig GRACE INERTIA Plug



TE Part # 2-1903393-3 GIC 2.5 W CAP HSG 4P BLUE



TE Part # 1-1903393-2 GIC 2.5 W CAP HSG 4P RED



TE Part # 1903393-1 GIC 2.5 W CAP HSG 4P NATURAL



Also in the Series | GRACE INERTIA 2.5



Rectangular Connector Housings, Wire-to-Wire, 4 Position, .098 in [2.5 mm] Centerline, 1 Row, PBT GF, Plug, Socket, Wire & Cable, GRACE INERTIA 2.5





Customers Also Bought



POWER DBL LOCK PLATE 3P /6.5MM	2.5 SIGNAL D/LOCK D.L.P 4P	2.5 SIGNAL DBL LOCK REC CONT M	GRACE INERTIA CONNECTOR 3.5 2P



Documents

Product Drawings GIC 2.5 W PLUG HSG 4P RED

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1903390-2_F_c-1-1903390-2-f.2d_dxf.zip

Rectangular Connector Housings, Wire-to-Wire, 4 Position, .098 in [2.5 mm] Centerline, 1 Row, PBT GF, Plug, Socket, Wire & Cable, GRACE INERTIA 2.5



English

Customer View Model ENG_CVM_CVM_1-1903390-2_F_c-1-1903390-2-f.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1903390-2_F_c-1-1903390-2-f.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English

Product Environmental Compliance Product Compliance

English

Product Compliance

English