

# SACC-SQ-M12MS-5CON-20/0,5-0,08 - Device connector front mounting



1419983

<https://www.phoenixcontact.com/us/products/1419983>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector front mounting, 5-position, M12, coding: A , Individual wires, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1239289

## Commercial data

Item number	1419983
Packing unit	1 pc
Minimum order quantity	50 pc
Sales key	AB24
Product key	ABQCED
GTIN	4055626200361
Weight per piece (including packing)	23.6 g
Weight per piece (excluding packing)	14.2 g
Customs tariff number	85366990
Country of origin	DE

# SACC-SQ-M12MS-5CON-20/0,5-0,08 - Device connector front mounting



1419983

<https://www.phoenixcontact.com/us/products/1419983>

## Technical data

### Notes

#### Safety note

Safety note

WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.

- WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.

- The products are suitable for applications in plant, controller, and electrical device engineering.

- When operating the connectors in outdoor applications, they must be separately protected against environmental influences.

- Assembled products may not be manipulated or improperly opened.

- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at [phoenixcontact.com/products](https://www.phoenixcontact.com/products)).

- When using the product in direct connection with third-party manufacturers, the user is responsible.

- For operating voltages > 50 V AC, conductive connector housings must be grounded

- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.

- Observe the corresponding technical data. You will find information:
  - o On the product
  - o On the packing label
  - o In the supplied documentation
  - o Online at [phoenixcontact.com/products](https://www.phoenixcontact.com/products) under the product

- Only use tools recommended by Phoenix Contact

- Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at [phoenixcontact.com/products](https://www.phoenixcontact.com/products)

- Ensure that the protective or functional ground has been properly connected.

- VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector

- The connector warms up in normal operation. Depending on the

# SACC-SQ-M12MS-5CON-20/0,5-0,08 - Device connector front mounting



1419983

<https://www.phoenixcontact.com/us/products/1419983>

ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).

## Mounting

Mounting type	Front/square flange mounting
Connection method	Individual wires

## Product properties

Product type	Circular connectors (device side)
Number of positions	5
Coding	A

### Insulation characteristics

Overvoltage category	III
Degree of pollution	3

## Electrical properties

Rated surge voltage	1.5 kV AC
Nominal voltage $U_N$	60 V
Nominal current $I_N$	4 A

## Connection data

### Conductor connection

Connection method	Individual wires
Contact connection type	Crimp contacts
Conductor cross section	0.08

## Cable/line

Cable length	0.5
--------------	-----

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-25 ... -85

## Standards and regulations

Standards/specifications	according to IEC 61076-2-101
--------------------------	------------------------------

# SACC-SQ-M12MS-5CON-20/0,5-0,08 - Device connector front mounting



1419983

<https://www.phoenixcontact.com/us/products/1419983>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1419983>



**EAC**

Approval ID: B.01687

# SACC-SQ-M12MS-5CON-20/0,5-0,08 - Device connector front mounting



1419983

<https://www.phoenixcontact.com/us/products/1419983>

## Classifications

### ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

### ETIM

ETIM 8.0	EC002635
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# SACC-SQ-M12MS-5CON-20/0,5-0,08 - Device connector front mounting



1419983

<https://www.phoenixcontact.com/us/products/1419983>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)