



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .250 (6.350mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .020 (.508mm)	F IN (mm) +/- .005 (.127mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING	
	MIN IN (mm)	MAX IN (mm)										
AP (R,L)-15-250-9	.355 (9.017mm)	4.075 (103.505mm)	14.938 (379.425mm)	.077 (1.960mm)	.477 (12.115mm)	.762 (19.354mm)	.384 (9.753mm)	.642 (16.306mm)	250 (1,150)	V-2	N/A	
AP (R, L)-15-250-0	.355 (9.017mm)	4.075 (103.505mm)	14.938 (379.425mm)	.077 (1.960mm)	.477 (12.115mm)	.762 (19.354mm)	.384 (9.753mm)	.642 (16.306mm)	250 (1,150)	V-2	N/A	
AP (R,L)-22-250-9	.355 (9.017mm)	6.615 (168.021mm)	22.875 (581.025mm)	.077 (1.960mm)	.481 (12.217mm)	.762 (19.354mm)	.387 (9.829mm)	.650 (16.510mm)	250 (1,150)	V-2	N/A	
AP (R, L)-22-250-0	.355 (9.017mm)	6.615 (168.021mm)	22.875 (581.025mm)	.077 (1.960mm)	.481 (12.217mm)	.762 (19.354mm)	.387 (9.829mm)	.650 (16.510mm)	250 (1,150)	V-2	N/A	
						250 LB. EXTRA HEAVY DUTY SERIES CABLE TIES						
						<b>COLOR DESIGNATIONS:</b> 0 = UV BLACK    9 = NATURAL			<b>MATERIAL:</b> <b>NYLON 6/6 POLYAMIDE</b>			
						SHEET 1 OF 1		<b>REV.: A</b>		DRAWING NO.: 250-A		
A	3/12/18	PB	EG	EG	INITIAL RELEASE		DRAWN BY		DATE		CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		PB		3/12/18		EG	NONE
<b>CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.</b>												
<b>THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.</b>												