

Specification Sheet

Part Number: 157-00212

All-in-one bundling and fastening solution reduces costs and assembly time.

Variety of fir tree diameters and offset lengths address most offset applications.

High-spec materials and superior design deliver excellent performance and value.



1-Pc Cable Tie/Fir Tree Mount with Disc, 12.5mm Offset, 8.5"L, M6 Hole, PA46, Brown, 500/bg

Article Number 157-00212

Type T50ROSFTM6SO12.5A

Color Brown (BN)

Quantity Per carton

Product Description HellermannTyton's offset fir tree cable tie family creates an offset routing solution for our customers who are moving away from using tape. The offset branch creates a strong offset that reduces flexing and shifting of the bundle.

Short Description 1-Pc Cable Tie/Fir Tree Mount with Disc, 12.5mm Offset, 8.5"L, M6 Hole, PA46, Brown, 500/bg

Global Part Name T50ROSFTM6SO12.5A-PA46-BN

| | |
|-------------------------------------|--------------------------|
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 225.0 |
| Length L (Imperial) | 8.5 |
| Length L (Metric) | 215.9 |
| Offset Length (Imperial) | 0.49 |
| Offset Length (Metric) | 12.5 |
| Fixation Method | Fir tree for round holes |
| Identification Plate Position | none |
| Releasable Closure | No |
| Width W (Imperial) | 0.19 |
| Width W (Metric) | 4.7 |
| Bundle Diameter Min (Imperial) | 0.08 |
| Bundle Diameter Min (Metric) | 2.0 |
| Bundle Diameter Max (Imperial) | 1.97 |
| Bundle Diameter Max (Metric) | 50.0 |
| Height H (Imperial) | 0.80 |

| | |
|---|-------|
| Height H (Metric) | 21.40 |
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.2 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 5.5 |
| Mounting Hole Diameter D (Imperial) | 0.24 |
| Mounting Hole Diameter D (Metric) | M6 |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Metric) | 6.0 |
| Disc Diameter (Metric) | 15.0 |
| Disc Diameter (Imperial) | 0.59 |

Material Polyamide 4.6 (PA46)

Material Shortcut PA46

Material Cable Tie Polyamide 4.6 (PA46)

| | |
|------------------------------|-----------------------------------|
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +266°F (-40°C to +130°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)