

MOV

Radial leaded metal oxide varistor



Product features

- Excellent surge current suppression
- Low leakage current
- 7, 10, 14, 20 mm disk type
- Encapsulation UL94-V0
- UL 1449 edition 4 IEC 61051-1/2
- Wide operating voltage range V_{RMS} 130 V to 680 V

Applications

- Smart meters
- Surge protective devices (SPD)
- Uninterruptible power supplies (UPS)
- Power distribution with integrated surge protection
- Power supplies and power converters
- Appliances

Agency information

- cURus: E340782 per UL1449
- TUV: J 50562561, J 50562664, J 50562779, J 50562785




Environmental compliance



Ordering part number

MOV 07 V130 Y -AP



Ordering part number

- Blank (bulk)
- AP (Ammo pack)



Powering Business Worldwide

Electrical characteristics (+25 °C)

Part number	Varistor voltage ¹ V1mA (V)	Max. operating voltage		Max. clamping voltage		Max. surge current 8/20 μs 1 time (A)	Rated power (W)	Max. capacitance @ 1 KHz (pF)	Max. energy (10/1000 μs) (J)	T max. (mm)	cURus	TUV
		V _{RMS} (V)	V _{DC} (V)	I _p (8/20 μs) (A)	V _p (V)							
MOV07V130	200	130	170	10	340	1200	0.25	250	13	4	√	√
MOV07V140	220	140	180	10	360	1200	0.25	230	14	4	√	√
MOV07V150	240	150	200	10	395	1200	0.25	210	15	4	√	√
MOV07V175	270	175	225	10	455	1200	0.25	185	18	4.5	√	√
MOV07V190	300	190	250	10	500	1200	0.25	165	20	4.5	√	√
MOV07V210	330	210	275	10	550	1200	0.25	150	23	4.5	√	√
MOV07V230	360	230	300	10	595	1200	0.25	140	24	4.5	√	√
MOV07V250	390	250	320	10	650	1200	0.25	130	26	5	√	√
MOV07V275	430	275	350	10	710	1200	0.25	115	28	5	√	√
MOV07V300	470	300	385	10	775	1200	0.25	105	29	5	√	√
MOV07V320	510	320	415	10	845	1200	0.25	100	31	5.5	√	√
MOV07V350	560	350	460	10	925	1200	0.25	90	35	5.5	√	√
MOV07V385	620	385	505	10	1025	1200	0.25	80	38	6	√	√
MOV07V420	680	420	560	10	1120	1200	0.25	75	42	6	√	√
MOV07V510	820	510	670	10	1355	1200	0.25	60	52	6.5	√	√
MOV10V130	200	130	170	25	340	2500	0.4	500	30	4.5	√	√
MOV10V140	220	140	180	25	360	2500	0.4	450	32	4.5	√	√
MOV10V150	240	150	200	25	395	2500	0.4	420	35	4.5	√	√
MOV10V175	270	175	225	25	455	2500	0.4	370	37	5	√	√
MOV10V190	300	190	250	25	500	2500	0.4	330	40	5	√	√
MOV10V210	330	210	275	25	550	2500	0.4	300	43	5	√	√
MOV10V230	360	230	300	25	595	2500	0.4	280	47	5	√	√
MOV10V250	390	250	320	25	650	2500	0.4	260	60	5	√	√
MOV10V275	430	275	350	25	710	2500	0.4	230	65	5.5	√	√
MOV10V300	470	300	385	25	775	2500	0.4	210	67	5.5	√	√
MOV10V320	510	320	415	25	845	2500	0.4	200	69	6	√	√
MOV10V350	560	350	460	25	925	2500	0.4	180	70	6	√	√
MOV10V385	620	385	505	25	1025	2500	0.4	160	72	6.5	√	√
MOV10V420	680	420	560	25	1120	2500	0.4	150	75	6.5	√	√
MOV10V460	750	460	615	25	1240	2500	0.4	130	77	6.5	√	√
MOV10V510	820	510	670	25	1355	2500	0.4	120	85	7	√	√
MOV10V550	910	550	745	25	1500	2500	0.4	110	93	7.5	√	√
MOV10V625	1000	625	825	25	1650	2500	0.4	100	102	7.5	√	√
MOV14V130	200	130	170	50	340	4500	0.6	1000	57	4.5	√	√
MOV14V140	220	140	180	50	360	4500	0.6	900	60	4.5	√	√
MOV14V150	240	150	200	50	395	4500	0.6	830	63	4.5	√	√
MOV14V175	270	175	225	50	455	4500	0.6	740	70	5	√	√
MOV14V190	300	190	250	50	500	4500	0.6	670	77	5	√	√
MOV14V210	330	210	275	50	550	4500	0.6	610	85	5	√	√
MOV14V230	360	230	300	50	595	4500	0.6	560	93	5	√	√
MOV14V250	390	250	320	50	650	4500	0.6	510	100	5	√	√
MOV14V275	430	275	350	50	710	4500	0.6	460	115	5.5	√	√
MOV14V300	470	300	385	50	775	4500	0.6	430	118	5.5	√	√
MOV14V320	510	320	415	50	845	4500	0.6	390	121	6	√	√

Electrical characteristics (+25 °C)


Part number	Varistor voltage ¹	Max. operating voltage		Max. clamping voltage		Max. surge current 8/20 μs 1 time (A)	Rated power (W)	Max. capacitance @ 1 KHz (pF)	Max. energy (10/1000 μs) (J)	T max. (mm)	cURus	TUV
	V1mA (V)	V _{RMS} (V)	V _{DC} (V)	I _p (8/20 μs) (A)	V _p (V)							
MOV14V350	560	350	460	50	925	4500	0.6	360	125	6	√	√
MOV14V385	620	385	505	50	1025	4500	0.6	320	128	6.5	√	√
MOV14V420	680	420	560	50	1120	4500	0.6	290	130	6.5	√	√
MOV14V460	750	460	615	50	1240	4500	0.6	270	143	6.5	√	√
MOV14V510	820	510	670	50	1355	4500	0.6	240	157	7	√	√
MOV14V550	910	550	745	50	1500	4500	0.6	220	175	7.5	√	√
MOV14V625	1000	625	825	50	1650	4500	0.6	200	190	7.5	√	√
MOV20V130	200	130	170	100	340	6500	1	2000	95	5	√	√
MOV20V140	220	140	180	100	360	6500	1	1800	100	5	√	√
MOV20V150	240	150	200	100	395	6500	1	1650	108	5	√	√
MOV20V175	270	175	225	100	455	6500	1	1500	127	5	√	√
MOV20V190	300	190	250	100	500	6500	1	1300	136	5	√	√
MOV20V210	330	210	275	100	550	6500	1	1200	150	5.5	√	√
MOV20V230	360	230	300	100	595	6500	1	1100	163	5.5	√	√
MOV20V250	390	250	320	100	650	6500	1	1000	180	5.5	√	√
MOV20V275	430	275	350	100	710	6500	1	930	190	6	√	√
MOV20V300	470	300	385	100	775	6500	1	850	204	6	√	√
MOV20V320	510	320	415	100	845	6500	1	780	210	6	√	√
MOV20V350	560	350	460	100	925	6500	1	710	215	6.5	√	√
MOV20V385	620	385	505	100	1025	6500	1	650	224	7	√	√
MOV20V420	680	420	560	100	1120	6500	1	600	230	7	√	√
MOV20V460	750	460	615	100	1240	6500	1	530	255	7.5	√	√
MOV20V485	780	485	640	100	1290	6500	1	510	265	7.5	√	√
MOV20V510	820	510	670	100	1355	6500	1	500	282	7.5	√	√
MOV20V550	910	550	745	100	1500	6500	1	440	310	8	√	√
MOV20V625	1000	625	825	100	1650	6500	1	400	342	8	√	√
MOV20V680	1100	680	895	100	1815	6500	1	360	383	8.5	√	√

1. Varistor voltage tolerance: ±10%

2. Leakage current (@75% of V1 mA) : ≤20 μA

Dimensions- mm
Drawing not to scale


Y kink



Family	D max	T max	P	d	L (Bulk)	L (Ammo)	A max
MOV07	9.0	See Electrical characteristics table	5.0±0.5	0.6±0.5	3.5±0.5	17.5±1	14.0
MOV10	12.5		7.5±0.5	0.8±0.5	3.5±0.5	17.5±1	18.0
MOV14	16.5		7.5±0.5	0.8±0.5	3.5±0.5	17.5±1	22.5
MOV20	22.5		10.0±0.5	1.0±0.5	3.5±0.5	17.5±1	31.0

*Tin covered copper clad steel

Part marking




Item	Description	Content
1	Family name	MOV
2	Body size	07, 10, 14, 20
3	V _{RMS}	V130 = 130 Vac
4	V _{1mA} tolerance code	K = ±10%
5	Certification logo	cURus

General specifications


Operating temperature		-40 °C to +125 °C
Lead pull strength	IEC 60068-2-21	Gradually applying the force specified and keeping the unit fixed for 10±1 sec. 0.5 < d ≤0.8 10 N 0.8< d ≤1.25 20 N
Lead bending strength	IEC 60068-2-21	Hold specimen and apply the force specified below to each lead. Bend the specimen to 90°, then return to the original position. Repeat the procedure in the opposite direction. 0.5 < d ≤0.8 5 N 0.8< d ≤1.25 10 N
Vibration	IEC 60068-2-6	Frequency range: 10 to 55 Hz Amplitude: 0.75 mm Direction:3 mutually perpendicular directions, 2 hours each.
Solderability	IEC 60068-2-20	+245 ± 3 °C , 3 ± 0.3 second
Resistance to welding heat	IEC 60068-2-20	+260 ± 3 °C , 10 ± 1 second
Dielectric strength	IEC 61051-1	The two ends of the sample are connected together as an electrode, and the epoxy encapsulation body surrounding the sample with a metal ball is another electrode, and the voltage is applied for 2 minutes at 2500 V _{AC} .
Damp heat test	IEC 60068-2-78	+40 ± 2 °C , 90 to 95% RH , 1344 hours
Temperature cycling test	IEC 60068-2-14	The temperature abrupt change cycled for 5 cycles according to the following conditions.
		Step Temperature °C Time (minute)
		1 -40±3 30±3
		2 +25±5 5±3
		3 +125±2 30±3
4 +25±5 5±3		
High temperature load test	MIL-STD-202 Method 108	+125±2 °C, 1000±24 hours, at VDC (Maximum operating voltage)

V-I characteristics curves


MOV07V130~510




MOV10V130~625



MOV14V130~625




MOV20V130~680




Pulse rating curves


MOV07V130~510




MOV10V130~625



MOV14V130~625



MOV20V130~680




Packaging information

Quantity


Part number	Bulk (pcs/bag)	Inner box	Shipping box	Ammo/box	Shipping box
MOV07V130-250	1000	2000	16000	1,500	7500
MOV07V 275-350	1000	2000	16000	1,250	6250
MOV07V385-510	1000	2000	16000	1,250	6250
MOV10V130-250	500	1000	8000	1,250	6250
MOV10V275-420	500	1000	8000	1250	6250
MOV10V460-625	400	800	6400	1000	5000
MOV14V130-250	250	500	4000	500	2000
MOV14V275-320	250	500	4000	500	2000
MOV14V350-420	250	500	4000	500	2000
MOV14V460-625	200	400	3200	400	1600
MOV20V130-250	100	200	1600	500	2000
MOV20V275-320	100	200	1600	500	2000
MOV20V350-420	100	200	1600	500	2000
MOV20V460-625	50	100	800	300	1200

Ammo pack dimension - mm



Dimension	Tolerance	MOV07	MOV10	MOV14	MOV20
f	±0.5	5	7.5	7.5	10
P	±1.0	12.7	12.7	25	25.4
P0	±1.0	12.7	12.7	13	12.7
Δh	Max	2	2	2	2
W	±1.0	18	18	18	18
W1	±0.5	9	9	9	9
D0	±0.2	4	4	4	4
d	±0.05	0.6	0.8	0.8	1
H	±1.0	17.5	17.5	17.5	17.5
H1	Max	32.5	36.5	41	49.5
t	±0.2	0.5	0.5	0.5	0.5

Wave solder profile



Profile feature	Lead (Pb) free solder	
Preheat	$T_s(\max)$	130 °C ± 20 °C
	$T_s(\min)$	Room temperature
	t_s	30 to 90 sconds
Soldering	T_p	260 °C maximum
	t_p	< 10 seconds
	Ramp-down rate	3.5 °C/second maximum

Manual solder

+360 °C (3 seconds maximum by soldering iron, distance from varistor 2 mm minimum), generally manual/hand soldering is not recommended.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com/electronics

© 2023 Eaton
All Rights Reserved
Printed in USA
Publication No. ELX1287 BU-ELX22150
January 2023

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

