



**3 Type**

**A** Mounting from the front side

**Metric table**

Dimensions in: millimeters - inches

| <b>1</b>   | <b>2</b>   |            |             |            |              |            |            |               |            |               |            |            |            |            |            |           |  |
|------------|------------|------------|-------------|------------|--------------|------------|------------|---------------|------------|---------------|------------|------------|------------|------------|------------|-----------|--|
| $l_1$      | $l_2$      | $b$        | $d_1$       | $d_2$      | $d_3$<br>Pin | $h$        | $l_3$      | $l_4$<br>max. | $l_5$      | $l_6$<br>max. | $l_7$      | $l_8$      | $m_1$      | $m_2$      | $m_3$      | $t$       |  |
| 66<br>2.60 | 55<br>2.17 | 18<br>0.71 | 8.4<br>0.33 | 15<br>0.59 | 8<br>0.31    | 18<br>0.71 | 24<br>0.94 | 42<br>1.65    | 12<br>0.47 | 29<br>1.14    | 32<br>1.26 | 26<br>1.02 | 41<br>1.61 | 37<br>1.46 | -          | 9<br>0.35 |  |
| 91<br>3.58 | 55<br>2.17 | 18<br>0.71 | 8.4<br>0.33 | 15<br>0.59 | 8<br>0.31    | 18<br>0.71 | 24<br>0.94 | 67<br>2.64    | 12<br>0.47 | 29<br>1.14    | 32<br>1.26 | 51<br>2.01 | 41<br>1.61 | 37<br>1.46 | 25<br>0.98 | 9<br>0.35 |  |

**Specification**

- Body  
Steel, zinc plated, blue passivated finish **ST**
- Pin  
Brass, nickel plated
- Washer  
Brass, nickel plated
- **RoHS compliant**

**Information**

GN 129.3 hinges are used for doors that are flush with the frame on the outside and cannot be removed when assembled.

These hinges are mounted with DIN 912 socket cap screws. This allows any wall thicknesses on the housing or door to be realized via existing threads or through holes.

see also...

- *List of Hinge Types* → page QVX
- *Hinges GN 129* → page QVX

**How to order**

**GN 129.3-66-55-A-ST**

- 1** Width  $l_1$
- 2** Length  $l_2$
- 3** Type
- 4** Material