#### WWW.PHIHONG.COM



## **5W USB Medical Grade Adapter**







#### **Features**

- Meets DoE Level VI
- **MOOP Classification**
- Divider Mode Charging (2.7V to Pin2, 2V to Pin3)
- LPS Compliant
- OVP, OCP, SCP

#### **Applications**

- Blood Glucose Meters
- **Blood Pressure Monitors**

Wearable Monitoring Devices

- **Safety Approvals** 
  - AAMI/ANSI ES 60601-1

- IEC60601-1
- IEC60601-1-11

#### **Mechanical Characteristics**

- Length: 47mm (1.85in)
- Width: 37.9mm (1.49in)

# Height: 22.3mm (0.88in)

Weight: 40g (1.41oz)

### **Output Specifications**

	DC	Load		Ripple <sup>1</sup>	Regulation	Case
Model	Output Voltage	Min.	Max.	P-P (max.)	Line & Load <sup>2</sup>	Color
MQ05A-050A-H <sup>3</sup>	5V	0A	1A	200mV	±5%	Black
MQ05A-050AW-H	5V	0A	1A	200mV	±5%	White

#### Notes:

- Measured with by-pass capacitors 0.1uF/10uF at output connector terminal and oscilloscope set at 20 MHz bandwidth. Requires 10mins burn-in at max load at cold start condition when testing at 0°C
- Output voltage measured on 1000mm long cable having #22AWG wires and at USB Micro-B connector
- Special order item. Minimum order quantity applies

## MQ05A-050A-H Characteristics<sup>1</sup>

#### **WWW.PHIHONG.COM**

**Input:** 

**AC** Input Voltage Rating

100 to 240V AC

**AC Input Voltage Range** 

90 to 264V AC

**AC Input Current** 

0.15A(RMS) max

**Leakage Current** 

5uA max

Input Power Saving<sup>2</sup>

≤30mW @115VAC/230VAC no load

**Output:** 

**Efficiency** 

DOE Level VI COC V5 Tier 2

**Environmental:** 

**Temperature** 

Operation  $0^{\circ}\text{C}$  to  $+40^{\circ}\text{C}$ Non-operation  $-40^{\circ}\text{C}$  to  $+85^{\circ}$ 

Relative Humidity 90%

**Emissions** 

Complies with FCC Class B

Complies with CAN ICES-001(B)/NMB-001(B)

**Immunity** 

ESD EN61000-4-2 Level 4

Surge EN61000-4-5 Level 3

Dielectric Withstand (Hi-pot) Test

Pri. to Sec. 3000VAC 10mA for 1 Minute

**Insulation Resistance** 

Pri. to Sec.: >10M ohm 500VDC

**FEATURES:** 

**Over-Voltage Protection** 

7V max.

**Short-Circuit Protection** 

Auto-restart

**Over-Current Protection** 

105%~140%

**DC Output Connector** 


USB A:

Pin 1 = V+

Pin 2 = 2.68V

Pin 3 = 2V

Pin 4 = RTN



#### Notes:

- 1. The characteristics defined are at ambient temperature of 25°C unless otherwise specified
- 2. After 15 minutes warm-up.

# **Dimension Diagram Unit: mm**

