

Self-Protected Low Side Driver with In-Rush Current Management

NCV8415

The NCV8415 is a three terminal protected Low-Side Smart Discrete FET. The protection features include Delta Thermal Shutdown, overcurrent, overtemperature, ESD and integrated Drain-to-Gate clamping for overvoltage protection. The device also offers fault indication via the gate pin. This device is suitable for harsh automotive environments.

Features

- Short-Circuit Protection with In-Rush Current Management
- Delta Thermal Shutdown
- Thermal Shutdown with Automatic Restart
- Overvoltage Protection
- Integrated Clamp for Overvoltage Protection and Inductive Switching
- ESD Protection
- dV/dt Robustness
- Analog Drive Capability (Logic Level Input)
- NCV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Grade 1 Qualified and PPAP Capable
- These Devices are Pb-Free and are RoHS Compliant

Typical Applications

- Switch a Variety of Resistive, Inductive and Capacitive Loads
- Can Replace Electromechanical Relays and Discrete Circuits
- Automotive / Industrial




Figure 1. Block Diagram




ON Semiconductor®

www.onsemi.com

| V _{DSS} (Clamped) | R _{DS(ON)} TYP | I _D MAX (Limited) |
|----------------------------|-------------------------|------------------------------|
| 42 V | 80 mΩ @ 10 V | 11 A |




SOT-223
CASE 318E
STYLE 3



DPAK
CASE 369C
STYLE 2


MARKING DIAGRAMS



SOT-223

Pin Marking Information

- 1 = Gate
- 2 = Drain
- 3 = Source
- 4 = Drain



DPAK

- A = Assembly Location
- Y = Year
- W, WW = Work Week
- G or ■ = Pb-Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

| Device | Package | Shipping† |
|--------------|-------------------|--------------------|
| NCV8415DTRKG | DPAK (Pb-Free) | 2500 / Tape & Reel |
| NCV8415STT1G | SOT-223 (Pb-Free) | 1000 / Tape & Reel |
| NCV8415STT3G | SOT-223 (Pb-Free) | 4000 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

MAXIMUM RATINGS

| Rating | Symbol | Value | Unit |
|---|---|----------------------|--------------------|
| Drain-to-Source Voltage Internally Clamped | V_{DSS} | 42 | V |
| Drain-to-Gate Voltage Internally Clamped | V_{DG} | 42 | V |
| Gate-to-Source Voltage | V_{GS} | ± 14 | V |
| Drain Current - Continuous | I_D | Internally Limited | |
| Total Power Dissipation (SOT-223) @ $T_A = 25^\circ\text{C}$ (Note 1) @ $T_A = 25^\circ\text{C}$ (Note 2) | P_D | 1.29 | W |
| | | 2.20 | |
| Total Power Dissipation (DPAK) @ $T_A = 25^\circ\text{C}$ (Note 1) @ $T_A = 25^\circ\text{C}$ (Note 2) | | 1.54 | |
| | | 2.99 | |
| Thermal Resistance (SOT-223) Junction-to-Ambient (Note 1) Junction-to-Ambient (Note 2) Junction-to-Case (Soldering Point) | $R_{\theta JA}$ $R_{\theta JA}$ $R_{\theta JS}$ | 96.4 56.8 10.6 | $^\circ\text{C/W}$ |
| Thermal Resistance (DPAK) Junction-to-Ambient (Note 1) Junction-to-Ambient (Note 2) Junction-to-Case (Soldering Point) | $R_{\theta JA}$ $R_{\theta JA}$ $R_{\theta JS}$ | 80.8 41.8 3.2 | |
| Single Pulse Inductive Load Switching Energy ($L = 10\text{ mH}$, $I_{Lpeak} = 4.2\text{ A}$, $V_{GS} = 5\text{ V}$, $R_G = 25\ \Omega$, $T_{Jstart} = 25^\circ\text{C}$) | E_{AS} | 88 | mJ |
| Load Dump Voltage ($V_{GS} = 0$ and 10 V , $R_L = 10\ \Omega$) (Note 3) | U_S^* | 52 | V |
| Operating Junction Temperature | T_J | -40 to 150 | $^\circ\text{C}$ |
| Storage Temperature | $T_{storage}$ | -55 to 150 | $^\circ\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Mounted onto a $80 \times 80 \times 1.6\text{ mm}$ single layer FR4 board (100 sq mm, 1 oz. Cu, steady state).
2. Mounted onto a $80 \times 80 \times 1.6\text{ mm}$ single layer FR4 board (645 sq mm, 1 oz. Cu, steady state).
3. Load Dump Test B (with centralized load dump suppression) according to ISO16750-2 standard. Guaranteed by design. Not tested in production. Passed Class C according to ISO16750-1.

ESD ELECTRICAL CHARACTERISTICS (Note 4, 5)

| Parameter | Test Condition | Symbol | Min | Typ | Max | Unit |
|-------------------------------------|----------------------------|--------|------|-----|-----|------|
| Electro-Static Discharge Capability | Human Body Model (HBM) | ESD | 4000 | - | - | V |
| | Charged Device Model (CDM) | | 1000 | - | - | |

4. Not tested in production.
5. This device series incorporates ESD protection and is tested by the following methods:
 ESD Human Body Model tested per AEC-Q100-002 (JS-001-2017).
 Field Induced Charge Device Model ESD characterization is not performed on plastic molded packages with body sizes smaller than $2 \times 2\text{ mm}$ due to the inability of a small package body to acquire and retain enough charge to meet the minimum CDM discharge current waveform characteristic defined in JEDEC JS-002-2018.




Figure 2. Voltage and Current Convention

NCV8415

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

| Parameter | Test Condition | Symbol | Min | Typ | Max | Unit |
|-----------------------------------|--|----------------------|-----|-----|-----|------|
| OFF CHARACTERISTICS | | | | | | |
| Drain-to-Source Breakdown Voltage | V _{GS} = 0 V, I _D = 10 mA | V _{(BR)DSS} | 42 | 46 | 51 | V |
| | V _{GS} = 0 V, I _D = 10 mA, T _J = 150°C (Note 6) | | 42 | 44 | 51 | |
| Zero Gate Voltage Drain Current | V _{GS} = 0 V, V _{DS} = 32 V | I _{DSS} | - | 0.6 | 2.0 | μA |
| | V _{GS} = 0 V, V _{DS} = 32 V, T _J = 150°C (Note 6) | | - | 2.4 | 10 | |
| Gate Input Current | V _{GS} = 5 V, V _{DS} = 0 V | I _{GSS} | - | 50 | 70 | |

ON CHARACTERISTICS

| | | | | | | |
|--|--|-------------------------------------|-----|------|------|-------|
| Gate Threshold Voltage | V _{GS} = V _{DS} , I _D = 150 μA | V _{GS(th)} | 1.0 | 1.6 | 2.0 | V |
| Gate Threshold Temperature Coefficient | V _{GS} = V _{DS} , I _D = 150 μA (Note 6) | V _{GS(th)} /T _J | - | -4.0 | - | mV/°C |
| Static Drain-to-Source On Resistance | V _{GS} = 10 V, I _D = 1.4 A | R _{DS(ON)} | - | 80 | 100 | mΩ |
| | V _{GS} = 10 V, I _D = 1.4 A, T _J = 150°C (Note 6) | | - | 150 | 190 | |
| | V _{GS} = 5.0 V, I _D = 1.4 A | | - | 105 | 120 | |
| | V _{GS} = 5.0 V, I _D = 1.4 A, T _J = 150°C (Note 6) | | - | 185 | 210 | |
| | V _{GS} = 5.0 V, I _D = 0.5 A | | - | 105 | 120 | |
| | V _{GS} = 5.0 V, I _D = 0.5 A, T _J = 150°C (Note 6) | | - | 185 | 210 | |
| Source-Drain Forward On Voltage | I _S = 7 A, V _{GS} = 0 V | V _{SD} | - | 0.88 | 1.10 | V |

SWITCHING CHARACTERISTICS (Note 6)

| | | | | | | | |
|--|---|-------------------------------------|-----|------|----|----|------|
| Turn-On Time (10% V _{GS} to 90% I _D) | V _{GS} = 0 V to 5 V, V _{DD} = 12 V, I _D = 1 A | t _{ON} | - | 30 | 35 | μs | |
| Turn-Off Time (90% V _{GS} to 10% I _D) | | t _{OFF} | - | 44 | 55 | | |
| Turn-On Time (10% V _{GS} to 90% I _D) | V _{GS} = 0 V to 10 V, V _{DD} = 12 V, I _D = 1 A | t _{ON} | - | 13 | 20 | μs | |
| Turn-Off Time (90% V _{GS} to 10% I _D) | | t _{OFF} | - | 70 | 90 | | |
| Turn-On Rise Time (10% I _D to 90% I _D) | | t _{rise} | - | 9 | 15 | | |
| Turn-Off Fall Time (90% I _D to 10% I _D) | | t _{fall} | - | 29 | 40 | | |
| Slew Rate On (80% V _{DS} to 50% V _{DS}) | | -dV _{DS} /dt _{ON} | 0.5 | 1.63 | - | | V/μs |
| Slew Rate Off (50% V _{DS} to 80% V _{DS}) | | dV _{DS} /dt _{OFF} | 0.4 | 0.55 | - | | |

SELF PROTECTION CHARACTERISTICS

| | | | | | | |
|------------------------------|---|-----------------------|-----|-----|-----|----|
| Current Limit | V _{GS} = 5 V, V _{DS} = 10 V | I _{LIM} | 7.0 | 8.8 | 11 | A |
| | V _{GS} = 5 V, V _{DS} = 10 V, T _J = 150°C (Note 6) | | 6.4 | 7.9 | 9.1 | |
| | V _{GS} = 10 V, V _{DS} = 10 V (Note 6) | | 5.2 | 8.2 | 11 | |
| | V _{GS} = 10 V, V _{DS} = 10 V, T _J = 150°C (Note 6) | | 5.0 | 7.4 | 10 | |
| Temperature Limit (Turn-Off) | V _{GS} = 5.0 V (Note 6) | T _{LIM(OFF)} | 150 | 175 | 185 | °C |
| Thermal Hysteresis | | ΔT _{LIM(ON)} | - | 15 | - | |
| Temperature Limit (Turn-Off) | V _{GS} = 10 V (Note 6) | T _{LIM(OFF)} | 150 | 185 | 200 | °C |
| Thermal Hysteresis | | ΔT _{LIM(ON)} | - | 15 | - | |

GATE INPUT CHARACTERISTICS (Note 6)

| | | | | | | |
|----------------------------------|--|------------------|-----|-----|-----|----|
| Device ON Gate Input Current | V _{GS} = 5 V, V _{DS} = 10 V, I _D = 1 A | I _{GON} | 35 | 50 | 70 | μA |
| | V _{GS} = 10 V, V _{DS} = 10 V, I _D = 1 A | | 250 | 310 | 450 | |
| Current Limit Gate Input Current | V _{GS} = 5 V, V _{DS} = 10 V | I _{GCL} | 45 | 76 | 95 | μA |
| | V _{GS} = 10 V, V _{DS} = 10 V | | 320 | 450 | 550 | |
| Thermal Limit Gate Input Current | V _{GS} = 5 V, V _{DS} = 10 V, I _D = 0 A | I _{GTL} | 210 | 240 | 260 | μA |
| | V _{GS} = 10 V, V _{DS} = 10 V, I _D = 0 A | | 620 | 700 | 830 | |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

6. Not subject to production testing.

TYPICAL PERFORMANCE CURVES




Figure 3. Single Pulse Maximum Switch-Off Current vs. Load Inductance




Figure 4. Single Pulse Maximum Switching Energy vs. Load Inductance




Figure 5. Single Pulse Maximum Inductive Switch-Off Current vs. Time in Avalanche




Figure 6. Single Pulse Maximum Inductive Switching Energy vs. Time in Avalanche




Figure 7. On-State Output Characteristics




Figure 8. Transfer Characteristics

TYPICAL PERFORMANCE CURVES




Figure 9. $R_{DS(ON)}$ vs. Gate-Source Voltage




Figure 10. $R_{DS(ON)}$ vs. Drain Current




Figure 11. Normalized $R_{DS(ON)}$ vs. Temperature




Figure 12. Current Limit vs. Gate-Source Voltage




Figure 13. Current Limit vs. Junction Temperature




Figure 14. Drain-to-Source Leakage Current

TYPICAL PERFORMANCE CURVES




Figure 15. Normalized Threshold Voltage vs. Temperature




Figure 16. Source-Drain Diode Forward Characteristics




Figure 17. Resistive Load Switching Time vs. Gate-Source Voltage




Figure 18. Resistive Load Switching Drain-Source Voltage Slope vs. Gate-Source Voltage




Figure 19. Resistive Load Switching Time vs. Gate Resistance




Figure 20. Resistive Load Switching Drain-Source Voltage Slope vs. Gate Resistance

TYPICAL PERFORMANCE CURVES




Figure 21. $R_{\theta JA}$ vs. Copper Area (SOT-223)




Figure 22. $R_{\theta JA}$ vs. Copper Area (DPAK)




Figure 23. Transient Thermal Resistance (SOT-223)




Figure 24. Transient Thermal Resistance (DPAK)

APPLICATION INFORMATION

Circuit Protection Features

The NCV8415 has three main protections. Current Limit, Thermal Shutdown and Delta Thermal Shutdown. These protections establish robustness of the NCV8415.

Current Limit and Short Circuit Protection

The NCV8415 has current sense element. In the event that the drain current reaches designed current limit level, integrated Current Limit protection establishes its constant level.

Delta Thermal Shutdown

Delta Thermal Shutdown (DTSD) Protection increases higher reliability of the NCV8415. DTSD consist of two independent temperature sensors – cold and hot sensors. The NCV8415 establishes a slow junction temperature rise by sensing the difference between the hot and cold sensors. ON/OFF output cycling is designed with hysteresis that results in a controlled saw tooth temperature profile (Figure 26). The die temperature slowly rises (DTSD) until the absolute temperature shutdown (TSD) is reached around 175°C.

Thermal Shutdown with Automatic Restart

Internal Thermal Shutdown (TSD) circuitry is provided to protect the NCV8415 in the event that the maximum

junction temperature is exceeded. When activated at typically 175°C, the NCV8415 turns off. This feature is provided to prevent failures from accidental overheating.

EMC Performance

To improve the EMC performance/robustness, connect a small ceramic capacitor to the drain pin as close to the device as possible according to Figure 25.




Figure 25. EMC Capacitor Placement

TEST CIRCUITS AND WAVEFORMS




Figure 26. Overload Protection Behavior

TEST CIRCUITS AND WAVEFORMS




Figure 27. Resistive Load Switching Test Circuit




Figure 28. Resistive Load Switching Waveforms

TEST CIRCUITS AND WAVEFORMS




Figure 29. Inductive Load Switching Test Circuit




Figure 30. Inductive Load Switching Waveforms

MECHANICAL CASE OUTLINE

PACKAGE DIMENSIONS




ON Semiconductor®



SCALE 1:1

SOT-223 (TO-261)
CASE 318E-04
ISSUE R


DATE 02 OCT 2018



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSIONS D & E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.200MM PER SIDE.
4. DATUMS A AND B ARE DETERMINED AT DATUM H.
5. A1 IS DEFINED AS THE VERTICAL DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT OF THE PACKAGE BODY.
6. POSITIONAL TOLERANCE APPLIES TO DIMENSIONS b AND b1.

| MILLIMETERS | | | |
|-------------|----------|------|------|
| DIM | MIN. | NOM. | MAX. |
| A | 1.50 | 1.63 | 1.75 |
| A1 | 0.02 | 0.06 | 0.10 |
| b | 0.60 | 0.75 | 0.89 |
| b1 | 2.90 | 3.06 | 3.20 |
| c | 0.24 | 0.29 | 0.35 |
| D | 6.30 | 6.50 | 6.70 |
| E | 3.30 | 3.50 | 3.70 |
| e | 2.30 BSC | | |
| L | 0.20 | --- | --- |
| L1 | 1.50 | 1.75 | 2.00 |
| He | 6.70 | 7.00 | 7.30 |
| θ | 0° | --- | 10° |



| | | |
|------------------|------------------|--|
| DOCUMENT NUMBER: | 98ASB42680B | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | SOT-223 (TO-261) | PAGE 1 OF 2 |


ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

SOT-223 (TO-261)
CASE 318E-04
ISSUE R

DATE 02 OCT 2018

- | | | | | |
|--|---|---|---|---|
| STYLE 1: PIN 1. BASE 2. COLLECTOR 3. EMITTER 4. COLLECTOR | STYLE 2: PIN 1. ANODE 2. CATHODE 3. NC 4. CATHODE | STYLE 3: PIN 1. GATE 2. DRAIN 3. SOURCE 4. DRAIN | STYLE 4: PIN 1. SOURCE 2. DRAIN 3. GATE 4. DRAIN | STYLE 5: PIN 1. DRAIN 2. GATE 3. SOURCE 4. GATE |
| STYLE 6: PIN 1. RETURN 2. INPUT 3. OUTPUT 4. INPUT | STYLE 7: PIN 1. ANODE 1 2. CATHODE 3. ANODE 2 4. CATHODE | STYLE 8: CANCELLED | STYLE 9: PIN 1. INPUT 2. GROUND 3. LOGIC 4. GROUND | STYLE 10: PIN 1. CATHODE 2. ANODE 3. GATE 4. ANODE |
| STYLE 11: PIN 1. MT 1 2. MT 2 3. GATE 4. MT 2 | STYLE 12: PIN 1. INPUT 2. OUTPUT 3. NC 4. OUTPUT | STYLE 13: PIN 1. GATE 2. COLLECTOR 3. EMITTER 4. COLLECTOR | | |

**GENERIC
 MARKING DIAGRAM***




- A = Assembly Location
- Y = Year
- W = Work Week
- XXXXX = Specific Device Code
- = Pb-Free Package

(Note: Microdot may be in either location)


*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

| | | |
|-------------------------|-------------------------|---|
| DOCUMENT NUMBER: | 98ASB42680B | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | SOT-223 (TO-261) | PAGE 2 OF 2 |

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

MECHANICAL CASE OUTLINE


PACKAGE DIMENSIONS




DPAK (SINGLE GAUGE) CASE 369C ISSUE G

DATE 31 MAY 2023


SCALE 1:1




TOP VIEW



SIDE VIEW




BOTTOM VIEW



BOTTOM VIEW

ALTERNATE CONSTRUCTIONS



RECOMMENDED MOUNTING FOOTPRINT*

*FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERM/D.


- | | | | | |
|--|--|---|---|--|
| STYLE 1: PIN 1. BASE 2. COLLECTOR 3. EMITTER 4. COLLECTOR | STYLE 2: PIN 1. GATE 2. DRAIN 3. SOURCE 4. DRAIN | STYLE 3: PIN 1. ANODE 2. CATHODE 3. ANODE 4. CATHODE | STYLE 4: PIN 1. CATHODE 2. ANODE 3. GATE 4. ANODE | STYLE 5: PIN 1. GATE 2. ANODE 3. CATHODE 4. ANODE |
| STYLE 6: PIN 1. MT1 2. MT2 3. GATE 4. MT2 | STYLE 7: PIN 1. GATE 2. COLLECTOR 3. EMITTER 4. COLLECTOR | STYLE 8: PIN 1. N/C 2. CATHODE 3. ANODE 4. CATHODE | STYLE 9: PIN 1. ANODE 2. CATHODE 3. RESISTOR ADJUST 4. CATHODE | STYLE 10: PIN 1. CATHODE 2. ANODE 3. CATHODE 4. ANODE |

NOTES:

- DIMENSIONING AND TOLERANCING ASME Y14.5M, 1994.
- CONTROLLING DIMENSION: INCHES
- THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3, AND Z.
- DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
- DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
- DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.
- OPTIONAL MOLD FEATURE.

| DIM | INCHES | | MILLIMETERS | |
|-----|--------|-------|-------------|-------|
| | MIN. | MAX. | MIN. | MAX. |
| A | 0.086 | 0.094 | 2.18 | 2.38 |
| A1 | 0.000 | 0.005 | 0.00 | 0.13 |
| b | 0.025 | 0.035 | 0.63 | 0.89 |
| b2 | 0.028 | 0.045 | 0.72 | 1.14 |
| b3 | 0.180 | 0.215 | 4.57 | 5.46 |
| c | 0.018 | 0.024 | 0.46 | 0.61 |
| c2 | 0.018 | 0.024 | 0.46 | 0.61 |
| D | 0.235 | 0.245 | 5.97 | 6.22 |
| E | 0.250 | 0.265 | 6.35 | 6.73 |
| e | 0.090 | BSC | 2.29 | BSC |
| H | 0.370 | 0.410 | 9.40 | 10.41 |
| L | 0.055 | 0.070 | 1.40 | 1.78 |
| L1 | 0.114 | REF | 2.90 | REF |
| L2 | 0.020 | BSC | 0.51 | BSC |
| L3 | 0.035 | 0.050 | 0.89 | 1.27 |
| L4 | --- | 0.040 | --- | 1.01 |
| Z | 0.155 | --- | 3.93 | --- |

GENERIC MARKING DIAGRAM*



- IC**
- XXXXXX = Device Code
 A = Assembly Location
 L = Wafer Lot
 Y = Year
 WW = Work Week
 G = Pb-Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "•", may or may not be present. Some products may not follow the Generic Marking.

| | | |
|-------------------------|----------------------------|---|
| DOCUMENT NUMBER: | 98AON10527D | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | DPAK (SINGLE GAUGE) | PAGE 1 OF 1 |

onsemi and Onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales