LABEL Dispensers

Electric

Additional info for LD6050

- Will dispense labels and die-cut parts
- Adjustable strip plate for hard-torelease labels
- Will accommodate core sizes of 1" (25 mm) and 3" (76mm)
- Automatically rewinds liner scrap for a cleaner working environment
- Liner scrap is easily removed
- No tools required for adjusting to different size labels
- No maintenance required
- For Clear labels please select Model # LD5100C

Additional info for LD6025

- Will dispense labels and die-cut parts
- Adjustable strip plate for hard-torelease labels
- Will accommodate core sizes of 1" (25 mm) and 3" (76mm)
- Can dispense paper, polyester, vinyl, acetate, foam, foil, etc.
- Automatically rewinds liner scrap for a cleaner working environment
- Liner scrap is easily removed
- No tools required for adjusting to different size labels
- No maintenance required
- All 230V machines are C€ Certified

SPECIAL APPLICATIONS

For Clear labels please select Model # LD6050C or LD6025C

Suggested accessory: LDHANGER16 16" (40.6cm) wide

See Accessories Pg. 31



For 230V machines, please add "-2" to the end of the model number. (Example: LD6050-2)

LD6050

4.5" (114mm) wide — Electric Label Dispenser "HIGH SPEED"

- Ideal for virtually any kind of label from bar code to packaging
- Automatically peels and advances labels
- New built-in hanging capability for use with workbenches and LDHANGER16
- Photosensor accuracy and reliability
- All metal construction
- High torque motor for heavy rolls of labels
- = Will dispense labels from .25" to 4.5" (6 to 114mm) in width
- Will dispense labels from .50" to 6" (13 to 152mm) in length
- Made in U.S.A.

















LD6025

4.5" (114mm) wide — Electric Label Dispenser

- = Ideal for short length and tiny bar code labels
- Automatically peels and advances labels
- New built-in hanging capability for use with workbenches and LDHANGER16
- Photosensor accuracy and reliability
- All metal construction
- = High torque motor for heavy rolls of labels
- Will dispense labels from .25" to 4.5" (6 to 114mm) in width
- Will dispense labels from .125" to 6" (3 to 152mm) in length
- Made in U.S.A.







labelm







MODEL #	Liner Capacity Width	Length	Roll Capacity	Feed Speed**	Dimensions	Electrical Requirements	Weight
LD6050	.25" to 4.5"	.50" to 6"	12"	3.3"/sec**	10.8"(L) x 10.8"(W) x 14.5"(H)	100/120V 50/60Hz, <1 amp	10.5 lbs
	(6mm to 114mm)	(13mm to 152mm)	(31cm)	(8cm/sec.)	27.4cm(L) x 27.4cm(W) x 36.8cm(H)	(230V 50/60Hz C€ available)	(4.76 kg)
LD6025	.25" to 4.5"	.125" to 6"	12"	1.6"/sec**	10.8"(L) x 13.2"(W) x 14.5"(H)	100/120V 50/60Hz, <1 amp	7.8 bs
	(6mm to 114mm)	(3mm to 152mm)	(31cm)	(3.9cm/sec.)	27.4cm(L) x 33.5cm(W) x 36.8cm(H)	(230V 50/60Hz C € available)	(3.5 kg)

^{*}LD6100 model specifications are the same as the above models, but the Feed Speed is 6.6"/Sec. **speed calculated at 60Hz