EMC Components Common Type Chip Beads SMD

This is a common type bead product that removes the noise components in a signal line and includes beads for two lines in a single chip. The product exhibits substantial impedance characteristics in the high frequency range and is therefore capable of effectively removing differential mode noises. Additionally, an appropriate amount of magnetic coupling is created between the beads of the two lines, giving the product the capability to remove not only differential mode noise but common mode noise as well. It is encased in a 1210 casing. This is an SMD product that allows for automatic mounting by taping.

FEATURES

- Compact size, Low Rdc (0.75Ω max.)
- · Capable of removing both common and differential mode noises.
- · Closed magnetic circuit structure allows high-density installation while preventing crosstalk between circuits.

APPLICATIONS

Audio signal lines used in cell phones and mobile audio devices, personal computers and peripheral equipment, PDA, digital camera, etc.

PRODUCT IDENTIFICATION

MCZ 1210 A D 102 T (2) (3) (4) (5) (6)(1)


- (1) Series name
- (2) Dimensions L×W
- (3) Ferrite material
- (4) Number of line
- (5) Impedance
- 102:1000 Ω at 100MHz
- (6) Packaging style T:Taping


ELECTRICAL CHARACTERISTICS

| MCZ Series | MCZ1210 | Гуре |
|------------|---------|------|
| | | |

Size: JIS/IEC 1210, EIA 0504

SHAPES AND DIMENSIONS/RECOMMENDED PC BOARD PATTERN







CIRCUIT DIAGRAM



PACKAGING STYLE AND QUANTITIES


| Packaging style | Quantity |
|-----------------|------------------|
| Taping | 4000 pieces/reel |

| Part No. | Open mode impedance (Ω)[at 100MHz] | DC resistance (Ω)max. | Insulation resistance (MΩ)min. | Rated voltage Edc(V)max. | Rated current Idc(mA)max. |
|--------------|---------------------------------------|--------------------------|--------------------------------|-----------------------------|------------------------------|
| MCZ1210AD102 | 1000±25% | 0.75 | 1 | 5 | 50 |
| MCZ1210AD221 | 220±25% | 0.3 | 1 | 5 | 350 |
| MCZ1210AD121 | 120±25% | 0.2 | 1 | 5 | 500 |


EMC Components

Common Type Chip Beads SMD


TYPICAL ELECTRICAL CHARACTERISTICS IMPEDANCE vs. FREQUENCY CHARACTERISTICS MCZ1210AD102



MCZ1210AD121



MEASURING CIRCUITS



MCZ Series MCZ1210 Type

Size: JIS/IEC 1210, EIA 0504

MCZ1210AD221

