

T300-27K-12V-R16-KIT
 T300-30K-12V-R16-KIT
 T300-52K-12V-R16-KIT

2.2W White LED Tape Light Kit, Standard Output

SPECIFICATION:

Input Voltage	12 VDC
Wattage	2.2 W/ft
Output	<div style="display: flex; align-items: center;"> <div style="width: 15px; height: 15px; background-color: #f0e68c; margin-right: 5px;"></div> 2700K - 208 lm/ft <div style="width: 15px; height: 15px; background-color: #fff9c4; margin-right: 5px; margin-left: 5px;"></div> 3000K - 214 lm/ft <div style="width: 15px; height: 15px; background-color: #e0f2f1; margin-right: 5px; margin-left: 5px;"></div> 5200K - 230 lm/ft </div>
CRI	90+
Dimmable	0-10V, ELV, MLV
Max. Run Length	16 ft
Field Cuttable	3.9" cut points
Beam Angle	120°
LED Tape Operating Temp.	-13°F to 140°F
LED Tape Warranty	5 year limited*
LED Tape Lifetime	50,000 hours
LED Tape Adhesive	3M™ VHB mounting adhesive on back
LED Tape Dimensions	0.39" W x 0.08" H (10mm x 2.0mm)
Incl. Power Supply	120VAC to 12VDC, 72W Capacity
IP Rating	IP20 - dry locations only



HIGH QUALITY
LED LIGHTING KITS



Applications:

- Indoor Signage
- Indirect Lighting
- Accent Lighting
- Undercabinet Lighting
- Furniture Accents

INCLUDED IN KIT



T300-XXK-12V-R16
16FT TAPELIGHT REEL

1 OF EACH



P72W12V
12V POWER SUPPLY

1 OF EACH



GRIPPER-TT-SC
GRIPPER-TW-SC

2 OF EACH

T300-27K-12V-R16-KIT

T300-30K-12V-R16-KIT

T300-52K-12V-R16-KIT

2.2W White LED Tape Light Kit, Standard Output

SPECIFICATION:

