

T30L0UVC2

Standard Cable Tie, 7.8" Long, 30lb Tensile Strength, PA66UV, Black, 100/pkg

Article Number: 111-00437

Part Number: T30L0UVC2

Type: T30L

[Find a Distributor](#)

[Order Samples](#)

[Get Technical Drawings](#)

Share

- ▶ [Cable Ties](#)
- ▶ [Cable Ties with Fasteners](#)
- ▶ [Cable Tie Tools](#)
- ▶ [Clamps and Clips](#)
- ▶ [Heatshrink Moulded Shapes](#)
- ▶ [Mounts](#)
- ▶ [Heavy Duty Mounts](#)
- ▶ [Wire Connectors](#)
- ▶ [Wiring Duct](#)
- ▶ [Wiring Protection](#)
- ▶ [Labels, Printers and Software](#)
- ▶ [Pre-Terminated Networking](#)
- ▶ [Copper Network Solutions](#)
- ▶ [Fiber Network Solutions](#)
- ▶ [Jacks and Wall Plates](#)
- ▶ [Racks - Cable Management](#)
- ▶ [Surface Raceway Systems](#)

Base Data

Part No.	T30L0UVC2
Type	T30L
Color	Black (BK)
Features	<ul style="list-style-type: none"> • UV stabilized cable ties contain an inhibitor which prolongs the life of the tie in UV exposures . • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Application Method	Quick, simple fixing by hand or with HellermannTyton tensioning tools
Identification Plate Position	none
Releasable Closure (Yes/ No)	No
Tie Closure	plastic pawl
Typical Application	Used to bundle and secure wire and cable.
Variant	Inside Serrated

Product Dimensions

Min. Tensile Strength	30.0lbs / 135.0N
Length (L)	198.0mm
Width (W)	3.6mm
Min. Ø Bundle	1.5mm
Max. Ø Bundle	50.0mm

Material and Specifications

Material	Polyamide 6.6 UV-resistant (PA66UV)
Flammability	UL94 V2
Material Specification	HF / RoHS
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	
Specification	UL ZODZ2.E64139
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No

 **Logistic and Packaging**

Packaging Type	bag
Pkg. Qty.	100
UPC	089306272588

[Find a Distributor](#)

[Get Product Samples](#)

[Get Technical Drawings](#)

[Home](#) | [About HellermannTyton](#) | [Products](#) | [Careers](#) | [Contact](#) | [Terms](#)

© HellermannTyton North America 2011 | [TS16949](#), [ISO 9001](#) and [ISO 14001 Certified](#)
7930 N. Faulkner Rd. Milwaukee, WI 53224-9517 | Fax: 800-848-9866 | Phone: 800-537-1512