



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Composite
- Shell Plating : Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +200°C
- Salt Spray : 2000 hours

| Connector dimension |             |
|---------------------|-------------|
| Dim                 | Nominal     |
| P                   | 3.25±0.2    |
| PP                  | 4.93±0.2    |
| R1                  | 23.01       |
| R2                  | 20.62       |
| S                   | 28.6±0.3    |
| V'                  | 19.5+1.4/-0 |
| W'                  | 2.1/3.65    |
| Z'                  | 32 Max      |
| VV THREAD           | M18x1-6g    |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D013M35HN**

|              |            |                          |                         |
|--------------|------------|--------------------------|-------------------------|
| A            | 15-10-2016 | First Release            |                         |
| ISS          | DATE       | Latest modification - by | MOD N°                  |
| Designed By: |            | Date:                    | <b>CUSTOMER DRAWING</b> |


**TITLE** Composite Receptacle 8D series

|       |  |                            |                 |
|-------|--|----------------------------|-----------------|
| SCALE |  | General linear Tolerances: | NPRDS / PROJECT |
| NA    |  | ±--                        | <b>859</b>      |

**SOURIAU** [WWW.SOURIAU.COM](http://WWW.SOURIAU.COM)

This document is the property of SOURIAU it must not be reproduced or communicated without permission

|           |                                    |  |            |
|-----------|------------------------------------|--|------------|
| FORMAT    | <b>SOURIAU DRG N° 8D013M35HN-C</b> |  | SHEET      |
| <b>A3</b> |                                    |  | <b>1/2</b> |



Contact Layout



| Contacts<br>(Insert arrangement 13-35) |             |             |                     |             |             |
|--|-------------|-------------|---------------------|-------------|-------------|
| Contact position ID                    | Location    |             | Contact position ID | Location    |             |
|  | X-axis (mm) | Y-axis (mm) |                     | X-axis (mm) | Y-axis (mm) |
| 1                                      | +045 (1.14) | +197 (5.00) | 12                  | -182 (4.62) | +088 (2.24) |
| 2                                      | +126 (3.20) | +158 (4.01) | 13                  | -126 (3.20) | +158 (4.01) |
| 3                                      | +182 (4.62) | +088 (2.24) | 14                  | -045 (1.14) | +197 (5.00) |
| 4                                      | +203 (5.16) | +000 (0.00) | 15                  | +045 (1.14) | +107 (2.72) |
| 5                                      | +182 (4.62) | -088 (2.24) | 16                  | +117 (2.97) | +026 (0.66) |
| 6                                      | +126 (3.20) | -158 (4.01) | 17                  | +093 (2.36) | -075 (1.91) |
| 7                                      | +045 (1.14) | -197 (5.00) | 18                  | +000 (0.00) | -120 (3.05) |
| 8                                      | -045 (1.14) | -197 (5.00) | 19                  | -093 (2.36) | -075 (1.91) |
| 9                                      | -126 (3.20) | -158 (4.01) | 20                  | -117 (2.97) | +026 (0.66) |
| 10                                     | -182 (4.62) | -088 (2.24) | 21                  | -045 (1.14) | +107 (2.72) |
| 11                                     | -203 (5.16) | +000 (0.00) | 22                  | +000 (0.00) | -030 (0.76) |

| (Applicable to MIL-DTL-38999 only) |                 |                    |               |                |                  |            |
|------------------------------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| Shell size                         | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
| 13                                 | -35             | 22                 | 22D           | M              | All              | MS27527-35 |

Panel Cutout



| Dim | Nominal    |
|-----|------------|
| ØA  | 23.42 min  |
| ØAA | 19.05 min  |
| R1  | 23.01      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D013M35HN

|                |                                       |                                |   |
|----------------|---------------------------------------|--------------------------------|---|
| A              | 15-10-2016                            | First Release                  |   |
| ISS            | DATE                                  | Latest modification - by       | MOD N°  |
| Designed By:   |                                       | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Composite Receptacle 8D series</b> |                                |   |
| SCALE          |                                       | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| NA             |                                       |                                |   |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D013M35HN-C</b>    |                                | SHEET<br>2/2  |