



TapeCase Ltd.
150 Gaylord St
Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Heavy Duty Silicone Splicing

TC572 – Blue

General Description

High performance, heavy-duty splicing of silicone coated films and release liners. High temperature, with strong chemical resistance. Bonds well to low surface energy substrates.

Product Benefits

- Good temperature range
- Good Tack
- High Peel
- Bonds to low energy surfaces

Technical Data

TECHNICAL PROPERTIES	
Total Thickness	3.4 mil
Temperature Range	-65°F to +400°F
Color	Translucent Blue

ADHESIVE TEST DATA	
Peel Adhesion to Stainless Steel	40 oz./in
Adhesive	1.4 mil Silicone
Backing	2 mil Polyester

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.
3. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.