

AMP | AMP Twin-Leaf

TE Internal #: 583853-3


Connector Contact, Socket, Wire-to-Board, 24 – 20 AWG Wire Size, 404 – 1020 CMA Wire Size, .2 – .6 mm² Wire Size, Gold, Strip, AMP

Twin-Leaf

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Contacts



Contact Type: Socket

Connector System: Wire-to-Board

Centerline (Pitch): 2.54 mm, 3.18 mm, 3.96 mm [.156 in]

Contact Retention Type Within Housing

Housing Features

Centerline (Pitch)

Dimensions

Wire Size: 404 – 1020 CMA

Features

Product Type Features

Connector System	Wire-to-Board
Connector & Contact Terminates To	Wire & Cable
Contact Features	
Contact Retention Within Housing	With
	30 µin
Wire Contact Termination Area Plating Material	Tin-Lead
PCB Contact Termination Area Plating Material	Nickel
Contact Base Material	Phosphor Bronze
Contact Base Material Contact Type	Phosphor Bronze Socket
Contact Type	Socket
Contact Type Contact Mating Area Plating Material	Socket
Contact Type Contact Mating Area Plating Material Contact Current Rating (Max)	Socket

Locking Lance

2.54 mm, 3.18 mm, 3.96 mm[.156 in]



Compatible Insulation Diameter Range	1.22 – 1.52 mm[.048 – .06 in]
Wire Size	$.26 \text{ mm}^2$
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Circuit Application	Power & Signal
Identification Marking	
Wire Range Color Code	Green
Packaging Features	
Packaging Quantity	7000
Packaging Method	Strip

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Pb (13% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on



requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | AMP Twin-Leaf



Insertion & Extraction Tools(1)



Wire-to-Board Connector Assemblies & Housings(27)



Wire-to-Board Connector Contacts(15)

Customers Also Bought
























Documents

Product Drawings

TWIN LEAF TERM. STRIP CSTL

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_583853-3_BR.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_583853-3_BR.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_583853-3_BR.3d_stp.zip

English

Customer View Model

ENG_CVM_583853-3_V1.3d_igs.zip

English

Customer View Model

ENG_CVM_583853-3_V1.3d_stp.zip

English

3D PDF

English

Customer View Model

ENG_CVM_583853-3_V1.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English