



PC Board t=1.60mm
Component Side Shown

NOTES:
ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 50 MILLIOHMS MAX.
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH : 1000 VAC RMS 60HZ, 1MIN.
6. CATEGORY 5 CHARACTERISTIC:

Frequency	Near-End Cross Talk dB, MIN.	Return Loss dB, MIN.	Attenuation dB, MAX.
1.0 MHZ	65	23	0.1
4.0 MHZ	65	23	0.1
8.0 MHZ	62	23	0.1
10.0 MHZ	60	23	0.1
16.0 MHZ	56	23	0.2
20.0 MHZ	54	23	0.2
25.0 MHZ	52	14	0.2
31.25 MHZ	50	14	0.2
62.5 MHZ	44	14	0.3
100.0 MHZ	40	14	0.4

MECHANICAL:

1. HOUSING MATERIAL : GLASS FILLED NYLON UL94V-0 COLOR-BLACK.
2. INSERT & PLATE MATERIAL : GLASS FILLED NYLON UL94V-0 COLOR-BLACK.
3. CONTACT MATERIAL : PHOSPHOR BRONZE t=0.35mm.
4. PLATING : CONTACT AREA-SELECTIVE GOLD PLATING.
TAILS-TIN 150u" MIN OVER NICKEL.
5. OPERATING LIFE : 750 CYCLES MIN.
6. PCB RETENTION PRE-SOLDER : 1 LB MIN.
7. PCB RETENTION POST-SOLDER: 10 LBS MIN.

ENVIRONMENTAL:

1. STORAGE TEMPERATURE : -40°C TO +85°C.
2. OPERATION TEMPERATURE: -40°C TO +85°C.
3. WAVE SOLDERING TEMPERATURE: 255°C~265°C(5~10 SECONDS)
4. RoHS COMPLIANT.

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.
UL & CUL FILE NO. E163191

PART NUMBER	GOLD PLATING
E6588-A59122-L	6u"
E6588-A59124-L	30u"
E6588-A59125-L	50u"

DETACHED LISTS	← MM (INCH) →	RoHS Compliant				
	TOLERANCES EXCEPT AS NOTED		TITLE CAT.5 W/O GROUNDING STACKED GANGED JACK, 2X4			
	MM	±				
	.0 ± 0.2	±				
.00 ± 0.15	±					
.000 ± 0.075	±					
ANGLES ± 0.5		DFTO Cathy		DRAWING NO. CE653A41-LB		
THIRD ANGLE PROJECTION		DATE 09/19/2006		/PART NO. SEE TABLE		
		SCALE : 1.6 : 1		DO NOT SCALE DRAWING		
				SIZE A3	REV O	
				SHEET 1 OF		