



TapeCase Ltd.
150 Gaylord Street
Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Clear Polyester Tape

TC592 – Clear

General Description

TC592CL is a clear polyester film, single coated with a silicone pressure sensitive adhesive.

Applications

General purpose masking in powder coating applications

Product Benefits

- High temperature silicone adhesive
- Withstands 400°F baking cycles
- Removes cleanly after use

Technical Data

TECHNICAL PROPERTIES	
Total Thickness	3 mil
Temperature Range	-65°F to +400°F
Color	Clear

ADHESIVE TEST DATA	
Peel Adhesion to Stainless Steel	35 oz./in
Adhesive	1 mil Silicone
Backing	2 mil Polyester
Elongation	100%

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.
3. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.