



Product: <u>5320FN</u> ☑

Fire Alarm, #18-2c BC, Shielded, NPLF

Product Description

Fire Alarm Cable, Rated-NPLF, 2-18 AWG solid bare copper conductors with PVC/nylon insulation, overall Beldfoil® shield, PVC jacket with ripcord

Technical Specifications

Product Overview

| Suitable Applications: | Fire Alarm, Non-Power Limited, Circuits: Audio, Control, Initiating, Notification, Noisy Environment |
|------------------------|--|
| | |

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | No. of Conductors |
|-------|-------------|------------------|-------------------|
| 18 | Solid | BC - Bare Copper | 2 |
| Condu | ctor Count: | | 2 |

Insulation

| Material | Nominal Wall Thickness |
|--|------------------------|
| PVC/Nylon - Polyvinyl Chloride + Nylon | 0.021 in |

Color Chart

| Number | Color |
|--------|-------|
| 1 | Black |
| 2 | Red |

Outer Shield

| Type | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|----------------------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Таре | Bi-Laminate (Alum+Poly) | Beldfoil® | 100% | TC - Tinned Copper | 20 | Solid |

Outer Jacket

| Material | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|--------------------------|------------------|------------------------|---------|
| PVC - Polyvinyl Chloride | 0.243 in | 0.037 in | Yes |

Construction and Dimensions

Cabling



Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 6.5 Ohm/1000ft | 14.25 Ohm/1000ft |

Capacitance

Nom. Capacitance Conductor to Conductor Nom. Capacitance Conductor to Other Conductor to Shield



Inductance

Nominal Inductance
0.2 μH/ft

Current

Max. Recommended Current [A 5 Amps per Conductor at 25°C

Voltage

UL Voltage Rating 150 V RMS

Temperature Range

| UL Temp Rating: | 75°C |
|------------------------------|----------------|
| Operating Temperature Range: | -20°C To +75°C |

Mechanical Characteristics

| Bulk Cable Weight: | 30 lbs/1000ft |
|------------------------------|---------------|
| Max. Pull Tension: | 53.2 lbs |
| Min. Bend Radius/Minor Axis: | 2.5 in |

Standards

| NEC Articles: | Article 760 |
|----------------------|-------------|
| NEC/(UL) Compliance: | NPLF |

Applicable Environmental and Other Programs

| EU Directive 2000/53/EC (ELV): | Yes |
|-----------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (RoHS 2): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| MII Order #39 (China RoHS): | Yes |

Suitability

Suitability - Indoor: Yes

Flammability, LS0H, Toxicity Testing

| UL Flammability: | UL1685 UL Loading |
|--------------------|-------------------|
| UL voltage rating: | 150 V RMS |

Plenum/Non-Plenum

Plenum (Y/N): No

Related Part Numbers

Variants

| Item # | olor UPC | |
|----------------|-----------------|-----|
| 5320FN 0021000 | ted 61282516041 | 410 |
| ootnote: | | Ī |

History

| Update and Revision: | Revision Number: 0.312 Revision Date: 05-05-2023 |
|----------------------|--|

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.