

2202542

https://www.phoenixcontact.com/us/products/2202542

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Perfboard for the ME-MAX DEV-KIT; for 4-pos. MSTBO header; ideal for manual soldering



Your advantages

- Perfboard for self-assembly (for MSTBO headers)
- · Hole matrix dimension: 2.54 mm
- · Easy installation

Commercial data

Item number	2202542
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AC08
Product key	ACHABD
GTIN	4055626142302
Weight per piece (including packing)	30.5 g
Weight per piece (excluding packing)	29 g
Customs tariff number	85340019
Country of origin	DK



2202542

https://www.phoenixcontact.com/us/products/2202542

Technical data

Product properties

Product type	PCB
Product family	ME-MAX
Housing type	DIN rail housing
Housing series	ME-MAX

Dimensions

Width	95.2 mm
Height	99.2 mm
Depth	1.6 mm

Material specifications

Color	green
Housing material	FR 4-21

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	110 °C (depending on power dissipation)
---------------------------------	---



2202542

https://www.phoenixcontact.com/us/products/2202542

Classifications

ECLASS

	ECLASS-11.0	27182702
	ECLASS-13.0	27260692
ETIM		
	ETIM 8.0	EC001031
UNSPSC		
	UNSPSC 21.0	31261500



2202542

https://www.phoenixcontact.com/us/products/2202542

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



2202542

https://www.phoenixcontact.com/us/products/2202542

Accessories

ME MAX 22,5 2-2 DEV-KIT KMGY - Housing set

2202524

https://www.phoenixcontact.com/us/products/2202524



DEV-KIT ME MAX: contains 1 x ME MAX 22,5 2-2 housing and pluggable connection technology (4x MSTBO with 4x MSTBT), supplied in individual parts

ME 22,5 TBUS 1,5/5 VPE1 KMGY - DIN rail bus connectors

2202543

https://www.phoenixcontact.com/us/products/2202543



DIN rail connector, color: light grey, nominal current: 8 A (parallel contacts), rated voltage (III/2): 125 V, number of positions: 5, pitch: 3.81 mm, mounting: DIN rail mounting, locking: without, mounting: without, type of packaging: packed in cardboard, Item with gold-plated contacts, bus connectors for connecting with electronics housings, 5 parallel contacts

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com