

5

4



3

2



1

Positionierer im Set enthalten
Locator scope of delivery

BC 09 99 000 0630




FC 09 99 000 0631



Anwendungsbereich: FC1/BC/har-bus64 Kontakte
Application range: FC1/BC/har-bus64 contacts
Leiterquerschnitt: Profil 1: 0,09-0,20 mm²
wire gauge : Profil 2: 0,20-0,50 mm²

Crimpeinsätze Crimp dies



für har-bus 64 Crimpkontakte: / for har-bus 64 crimp contacts:

02 05 000 2513	Feder / female	2	0,09-0,5	28-20	0,7-1,5
02 05 000 1513	Feder / female	1	0,09-0,5	28-20	0,7-1,5


für BC Crimpkontakte: / for BC crimp contacts:

09 02 000 8484	Feder / female	2	0,09-0,5	28-20	0,7-1,5
09 02 000 8474	Feder / female	1	0,09-0,5	28-20	0,7-1,5

für FC1 Crimpkontakte: / for FC1 crimp contacts:

09 06 000 9574	Messer / male	2	0,09-0,25	28-24	0,7-1,5
09 06 000 9554	Messer / male	1	0,09-0,25	28-24	0,7-1,5
09 06 000 8484	Feder / female	2	0,09-0,25	28-24	0,7-1,5
09 06 000 8474	Feder / female	1	0,09-0,25	28-24	0,7-1,5
09 06 000 6464	Feder / female	Sn	0,09-0,25	28-24	0,7-1,5

Kontakt Nr. contact no.	Messer / Feder male / female	AFS PL	Leiterquerschnitt wire gauge	AWG AWG	Isolationsø Insulationø
----------------------------	---------------------------------	-----------	---------------------------------	------------	----------------------------



All Dimensions in mm
Original Size DIN A 4

Techn. Character.

Nicht tolerierte Maßel Free size tolerances

			Dat.	Name	Maßstab/Scale 1:1
			Detail.	Hage.	
			Insp.	Wae.	
35242	05.08.08	Wae	Stand.		
35122	17.04.08	Wae			
31239					
Mod.	Dat.	Name	HARTING Electronics GmbH & Co. KG D-32339 ESPELKAMP		



Crimp-Set FC1/BC/har-bus 64
für Zange 09 99 000 0620.00
for tool 09 99 000 0620.00

TB 09 99 000 0621

Blatt/ page

Sub.