

date 08/05/2022

page 1 of 3

SERIES: CDM810 | DESCRIPTION: M8 CONNECTOR

FEATURES

- · M8 male connector
- A & B code versions
- · panel mount
- IP67







SPECIFICATIONS

parameter conditions/description		min	typ	max	units
rated voltage	3 & 4 pole models 5, 6, & 8 pole models			60 30	V
rated current 3, 4, 6 5 pole models 6 8 8 pole models				3 1.5	A A
withstanding voltage for 1 minute			1,500		Vac
contact resistance				10	mΩ
insulation resistance at 500 Vdc for 1 minute		100			МΩ
insertion/withdrawal force		0.3		1.5	kgf
operating temperature		-25		80	°C
life		100			cycles
safety approvals compliant with IEC61076-2-104					
ammability rating see material table					
RoHS	yes				
IP level	IP67 (in mated condition)				
box QTY: 200 pcs per box packaging carton size: 270 x 215 x 107 mm carton QTY: 600 pcs per carton					

SOLDERABILITY

parameter conditions/description		min	typ	max	units
hand soldering	for maximum 3 seconds	360	380	400	°C

PART NUMBER KEY

CDM810 - XXX - MW - F810 - 050 - 67

Base Number

No. of Poles:

03A = 3 (A-Coding)

04A = 4 (A-Coding)

05B = 5 (B-Coding)


06A = 6 (A-Coding)

08A = 8 (A-Coding)

MECHANICAL DRAWING

units: mm tolerance: $0.5<X\le6.0$: ±0.1 mm $6.0<X\le30.0$: ±0.2 mm unless otherwise noted

ITEM	DESCRIPTION	MATERIAL	PLATING/COLOR
Α	M8x1.0 screw	brass	nickel
В	terminals; male	brass	gold
С	housing; male	PA66 (UL94V-0)	black
D	M8x1.0 nut	brass	nickel
Е	resin	epoxy resin	black
F	o-ring	FKM	black
G	wire	UL 1061 L=505 mm	



No. of Poles	3	4	5	6	8
A-Coding	A-Coding	2 • • • • • • • • • • • • • • • • • • •	2 • • • • • • • • • • • • • • • • • • •	4 3 3 5 6 6 6 1 6 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	6.5.4
Wire Size	24 AWG	24 AWG	24 AWG	26 AWG	26 AWG
Pin #					
1	brown	brown	brown	brown	white
2		white	white	white	brown
3	blue	blue	blue	blue	green
4	black	black	black	black	yellow
5			gray	gray	gray
6				pink	pink
7					blue
8					red

REVISION HISTORY

rev.	description	date
1.0	initial release	07/20/2022
1.01	logo, datasheet style update	08/05/2022

The revision history provided is for informational purposes only and is believed to be accurate.



CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.