



N= Number of contacts

A	(N-1)×3.81+14.2
B	(N-1)×3.81
2p-6p	±0.15
7p-12p	±0.20
13p-16p	±0.25
17p-24p	±0.30

SIGN	DATE	DESCRIPTION	APPROVER
△	04/20'06	Added feature	Marvin
△	8/16'06	Added VDE standard	Steady
△	1/12'07	Soldering temperature changed from 245° to 250°	Tony
△	12/27'07	Body flange is changed	Marvin
△	5/27'08	Operating temperature is changed	Marvin
△	2009.07.09	Body flange is changed	Jacke
△	2009.08.18	The material is changed	Jacke
△	2010.07.07	Remove the CSA mark	Chen Bo
△	11/17'11	Flange nut is changed	ChenMing
△	02/04-15	Add the product number & update the drawing	Evan

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material:
- Item ① Male contact pin: Copper C1100 Bright Tin plated over Nickel plated
 - Item ② Terminalhousing: Thermoplastic (UL94V-0)
 - Item ③ With flange nut: Brass M2.5
- Electrical: cULus /VDE
- Voltage rating: 300V/300V
 - Current rating: 10A/10.5A
 - Withstanding Voltage: 1.6 KV/2.5KV
 - Operating temperature: -40°C to +115°C
 - Soldering temperature: 260°C±5°C/5 Sec
 - Safety Approval:
 - Critical dimension: ▽

OQ xx 3 5 x 0 xxxx G

- No. OF POLES: 02: 2 POLES; 24: 24 POLES
- COLOR: 0 Black (RAL9005); 2 Red (RAL3001/D); 3 Orange(RAL2011/P); 4 Yellow(RAL1018/A); 5 Green(RAL6018/T); 6 Blue (RAL5015/A); 8 Grey(RAL7035/D); 9 White(RAL1102); C Green(RAL6018/U)
- G RoHS compliant (lead<4%) In copper Alloy
- 0000: "@" Logo (Standard)
- 000A: "ANYTEK" Mark
- 0091: "ANYTEK" Mark
- Any special item by customer request. please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		OQ 3.81mm 180° W/Flange Series 2p-24p				
PART NO.		OQxx35x0xxxxG		DWG NO.		80Q0603
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Evan			X. ±0.50
			02/04-15			X.X ±0.30
SHEET: 01/01				REV: N		X.XX ±0.10
						X° ±1°