

Connection element - ASI CC DIST FCAB 5M12 - 2741477

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Passive signal distributor, connection element, from flat-ribbon cable to 5 x M12 plug, e.g., for connecting up to 5 FLX AS-i M8 devices or 5 AS-i S-Line devices to the AS-i flat-ribbon cable

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	128.7 GRM
Custom tariff number	85366990
Country of origin	Germany

Technical data

Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C

General

Connection method	AS-i penetration technique
-------------------	----------------------------

Classifications

eCl@ss

eCl@ss 4.0	27250302
eCl@ss 4.1	27250281
eCl@ss 5.0	27259205
eCl@ss 5.1	27242692
eCl@ss 6.0	27242692
eCl@ss 7.0	27242692
eCl@ss 8.0	27242692

ETIM

ETIM 2.0	EC000313
----------	----------

Connection element - ASI CC DIST FCAB 5M12 - 2741477

Classifications

ETIM

ETIM 3.0	EC000313
ETIM 4.0	EC002584
ETIM 5.0	EC002584

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	39121311