

Protect It! Personal Charging Station with 3-Outlet Surge Protector, Direct Plug-In, 540 Joules, 4 USB Ports, 3 AC Outlets

MODEL NUMBER: SK34USBB



Provides reliable surge protection, charging, performance enhancement and convenient storage for mobile devices, such as tablets, MP3 players and smartphones. Ideal for home, office, workstations and hotel rooms.

Description

The SK34USBB Protect It! Personal Charging Station charges your sensitive electronics and protects them against surges, power fluctuations and EMI/RFI line noise that can damage devices and destroy data. Ideal for home, office, workstations, dorm rooms and hotel rooms, the SK34USBB features 540 joules of surge protection. Because of its small size and direct plug-in design, you can take it anywhere. With three NEMA 5-15R AC outlets and four USB ports with 4.8 total amps, the SK34USBB can charge multiple power-hungry devices, such as tablets, MP3 players and smartphones. A built-in top slot and an additional slide-out slot hold your devices to keep them safe and organized and avoid cable clutter. A diagnostic LED confirms protection status at a glance. An automatic shutoff feature permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required. Backed by \$10,000 of Ultimate Lifetime Insurance in the U.S., Canada and Puerto Rico only.

Features

Charges and Protects Your Portable Devices Charges mobile devices, such as tablets, MP3 players and smartphones
Ideal for home, office, workstations, dorm rooms and hotel rooms
540 joules protect against surges, power fluctuations and EMI/RFI line noise
Diagnostic LED confirms protection status at a glance
Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required
Direct plug-in design for easy transport anywhere

Easily Handles Multiple Devices 3 NEMA 5-15R outlets
4 USB charging ports (4.8A total)

Stores Mobile Devices While Charging Built-in top slot and additional pull-out slot hold 2 devices
Keeps devices safe and organized
Cuts down on cable clutter

Specifications

Highlights

- 3 NEMA 5-15R outlets
- 4 USB charging ports (4.8A total)
- 2 slots for holding tablets and smartphones
- 540 joules of surge protection

Package Includes

- SK34USBB Protect It! Personal Charging Station w/ 3-Outlet Surge Protector
- Owner's manual

| OVERVIEW | |
|--|------------------------------|
| UPC Code | 037332195319 |
| Product Type | Surge Protector |
| Charging Form Factor | Strip |
| Device Compatibility | Phone; Tablet; Amazon Kindle |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V |
| Input Plug Features | Right Angle (36D) |
| Input Cord Length Details | Direct Plug-In |
| Voltage Compatibility (VAC) | 120 |
| Input Plug Type | NEMA 5-15P |
| Input Cord Length (ft.) | 0 |
| Right-Angle Plug | No |
| Input Cord Length (m) | 0.00 |
| Integrated Cord Clip | No |
| OUTPUT | |
| Frequency Compatibility | 60 Hz |
| Output Receptacles | (3) 5-15R |
| Circuit Breaker (amps) | 15 |
| Transformer Accommodation | (2) Yes |
| Right-Angle Outlets | No |
| USER INTERFACE, ALERTS & CONTROLS | |
| Diagnostic LED(s) | Yes |
| CHARGING | |
| Number of Charging Ports | 4 |
| Total Charging Watts | 24 |
| Charging Method | USB |
| Charging Port Type | USB A (FEMALE) |
| Charging Ports / Amps | (4) 4.8A |
| Overcharge Protection | No |

| SURGE / NOISE SUPPRESSION | |
|--------------------------------------|--|
| AC Suppression Joule Rating | 540 |
| AC Suppression Response Time | < 1 ns |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| UL1449 Let Through Rating | 600, 700, 700 |
| EMI / RFI Filtering | Yes |
| Immunity | Conforms to IEE 587/ANSI C62.41 |
| Automatic Shut-Off | Yes |
| DATALINE SURGE SUPPRESSION | |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| Telephone/DSL Protection | No |
| PHYSICAL | |
| Material of Construction | Plastic |
| Power Cord Color | Black |
| Mounting Holes or Slots | No |
| Receptacle Color | Black |
| Shipping Dimensions (hwd / in.) | 2.80 x 4.10 x 5.60 |
| Shipping Dimensions (hwd / cm) | 7.11 x 10.41 x 14.22 |
| Shipping Weight (lbs.) | 0.70 |
| Shipping Weight (kg) | 0.32 |
| Unit Dimensions (hwd / in.) | 4.960 x 3.740 x 1.320 |
| Unit Dimensions (hwd / cm) | 12.6 x 9.5 x 3.35 |
| Unit Weight (lbs.) | 0.57 |
| Unit Weight (kg) | 0.26 |
| Input Cord Color | Black |
| FEATURES & SPECIFICATIONS | |
| Rotatable Outlets | No |
| Antimicrobial | No |
| GaN Technology | No |
| STANDARDS & COMPLIANCE | |
| Product Certifications | CAN/CSA-C22.2 No. 269.3 (Canada); NOM (Mexico); UL 1449; UL 497A |

| | |
|--|---|
| Product Compliance | RoHS |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$10,000 Ultimate Lifetime Insurance |