8-1971798-2 ACTIVE

GRACE INERTIA 2.5

TE Internal #: 8-1971798-2


PCB Mount Header, Vertical, Wire-to-Board, 8 Position, 2.5 mm [. 098 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder,

GRACE INERTIA 2.5

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > Glow Wire Sig GRACE INERTIA Header



Connector System: Wire-to-Board

Number of Positions: 8

Number of Rows: 1

Centerline (Pitch): 2.5 mm [.098 in]
PCB Mount Orientation: Vertical

All Glow Wire Sig GRACE INERTIA Header (39)

Features

Product Type Features

| Commonter Cuetam | Wire-to-Board |
|-----------------------------------|-----------------------|
| Connector System | vvire-to-board |
| Header Type | Fully Shrouded |
| Sealable | No |
| Connector & Contact Terminates To | Printed Circuit Board |
| PCB Connector Assembly Type | PCB Mount Header |
| Configuration Features | |
| Number of Positions | 8 |
| Number of Rows | 1 |
| PCB Mount Orientation | Vertical |
| Electrical Characteristics | |
| Operating Voltage | 50 VAC |



| Connector & Keying Code | В |
|---|-----------------------|
| Primary Product Color | Blue |
| Contact Features | |
| Mating Square Post Dimension | .5 mm[.02 in] |
| PCB Contact Termination Area Plating Material Thickness | 1 μm[39.37 μin] |
| Contact Layout | Inline |
| Mating Tab Width | .5 mm[.02 in] |
| Contact Underplating Material Thickness | 1.27 µm[50 µin] |
| Contact Mating Area Plating Material Thickness | 1 μm[39.37 μin] |
| PCB Contact Termination Area Plating Material Finish | Matte |
| Contact Shape & Form | Square |
| Contact Mating Area Plating Material Finish | Matte |
| Contact Underplating Material | Nickel |
| PCB Contact Termination Area Plating Material | Tin |
| Contact Base Material | Brass |
| Contact Mating Area Plating Material | Tin |
| Contact Type | Tab |
| Contact Current Rating (Max) | 3 A |
| ermination Features | |
| Rectangular Termination Post & Tail Thickness | .46 mm[.018 in] |
| Rectangular Termination Post & Tail Width | .46 mm[.018 in] |
| Termination Post & Tail Length | 3 mm[.118 in] |
| Termination Method to Printed Circuit Board | Through Hole - Solder |
| Mechanical Attachment | |
| PCB Mount Alignment Type | Locating Posts |
| Mating Alignment Type | Keyed |
| Mating Retention | With |
| PCB Mount Retention Type | Kinked |
| Mating Retention Type | Latch |
| Connector Mounting Type | Board Mount |
| Mating Alignment | With |
| PCB Mount Alignment | With |
| PCB Mount Retention | With |



Housing Features

| Housing Material | Nylon |
|-----------------------------|----------------------------|
| Centerline (Pitch) | 2.5 mm[.098 in] |
| Dimensions | |
| Connector Length | 22.5 mm[.88 in] |
| Connector Height | 8.8 mm[.34 in] |
| Connector Width | 7.38 mm[.29 in] |
| PCB Thickness (Recommended) | 1.6 mm[.063 in] |
| Usage Conditions | |
| Operating Temperature Range | -30 – 105 °C[-22 – 221 °F] |
| Operation/Application | |
| Circuit Application | Signal |
| Industry Standards | |
| Glow Wire Rating | Glow Wire |
| Agency/Standard | UL |
| Approved Standards | UL E28476 |
| UL Flammability Rating | UL 94V-0 |
| Packaging Features | |
| Packaging Quantity | 600 |
| | |

Product Compliance

Packaging Type

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not reviewed for solder process capability |

Bag, Box




Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts





Customers Also Bought

PCB Mount Header, Vertical, Wire-to-Board, 8 Position, 2.5 mm [.098 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, GRACE INERTIA 2.5





TE Part #1744057-6 3.96 EP HDR ASSY 6P W/PEGS



TE Part #3-2232546-3 STD Temp Sig GRACE INERTIA Header



TE Part #1-640389-4 14P MTA156 HDR ASSY SQ R/A F/L



TE Part #4-1123723-6 3.96 EP HDR ASSY 6P(RED)



TE Part #5-1123724-4
3.96EP HDR ASSY 4(7)P BLACK



TE Part #6-1123724-2 3.96EP HDR ASSY 2(3)P GREEN



TE Part #6-1123724-4 3.96EP HDR ASSY 4(7)P GREEN



TE Part #6-1971798-5

NEW GI CONN2.5 HDR ASMBLY 6P

BLK D1.0



Documents

Product Drawings

NEW GI CONN2.5 HDR ASMBLY 8P BLU D1.0

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_8-1971798-2_E_c-8-1971798-2-e.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_8-1971798-2_E_c-8-1971798-2-e.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_8-1971798-2_E_c-8-1971798-2-e.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

PCB Mount Header, Vertical, Wire-to-Board, 8 Position, 2.5 mm [.098 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, GRACE INERTIA 2.5



5-1773465-3-GI2.5Flyer

English

7-1773465-8-GI2.5-ChineseFlyer

Product Specifications

Application Specification

English