



### Equipment Jumper Kits

- Bond network equipment to grounding strip or grounding busbar
- Jumper kit available with both ends factory terminated to provide a bolt-on solution
- Jumper kit available with one end factory terminated to attach to the grounding strip or grounding busbar; free end accommodates unique equipment terminations

- Use jumpers with 90° bent lug, on grounding strip side, for high density grounding requirements up to one ground point per RU
- Use jumpers with 45° bent lugs, on grounding strip side, for improved cable management
- Engineered to comply with US and International grounding requirements



RGEJ1024PFY



RGEJ1057PFY



Part Number	Length In. (m)	Angle	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>#6 AWG (16mm<sup>2</sup>) Equipment Jumper Factory Terminated on One End for Switches, Cabinets, and 4-Post Racks</b>					
GJS660U	60 (1.52)	Straight	#6 AWG green wire with yellow horizontal stripe. Jumper is pre-terminated on one end with LCC6-14JAW-L.	1	10
GJS696U	96 (2.44)	Straight		1	10
<b>#10 AWG (6mm<sup>2</sup>) Equipment Jumpers Factory Terminated on Both Ends</b>					
RGEJ1024PHY	24 (0.61)	45°	#10 AWG (6mm <sup>2</sup> ) jumper; bent lug on grounding strip side to straight lug on equipment; provided with .16 oz. (5cc) of antioxidant and two each #12-24 x 1/2", M6 x 12mm, #10-32 x 1/2" and M5 x 12mm thread-forming screws.	1	10
RGEJ1024PFY	24 (0.61)	90°		1	10
RGEJ1036PFY	36 (0.91)	90°		1	10
RGEJ1024URT*	24 (0.61)	Straight	#10 AWG (6mm <sup>2</sup> ) jumper, 24 in. (609.6mm) L, pre-terminated with two #10 (5.3mm) stud hole ring terminals to provide a bolt-on solution for grounding network equipment.	1	10
<b>#6 AWG (16mm<sup>2</sup>) Equipment Jumpers Factory Terminated on Both Ends</b>					
RGEJ624PHY	24 (0.61)	45°	#6 AWG (16mm <sup>2</sup> ) jumper; bent lug on grounding strip side to straight lug on equipment; provided with .16 oz. (5cc) of antioxidant and two each #12-24 x 1/2", M6 x 12mm, #10-32 x 1/2" and M5 x 12mm thread-forming screws.	1	10
RGEJ624PFY	24 (0.61)	90°		1	10
RGEJ636PFY	36 (0.91)	90°		1	10
RGEJ660U*	60 (1.52)	Straight	#6 AWG (16mm <sup>2</sup> ) jumper, 60 in. (1524mm) L, pre-terminated with two straight slotted lugs to provide a bolt-on solution for grounding network equipment.	1	10
RGEJ696U*	96 (2.44)	Straight	#6 AWG (16mm <sup>2</sup> ) jumper, 96 in. (2438.4mm) L, pre-terminated with two straight slotted lugs to provide a bolt-on solution for grounding network equipment.	1	10
<b>#10 AWG (6mm<sup>2</sup>) Equipment Jumper Factory Terminated on One End</b>					
RGEJ1057PFY	57 (1.45)	90°	#10 AWG (6mm <sup>2</sup> ) jumper; bent lug on grounding strip side; provided with .16 oz. (5cc) of antioxidant and two each #12-24 x 1/2", M6 x 12mm, #10-32 x 1/2" and M5 x 12mm thread-forming screws.	1	10
<b>#6 AWG (16mm<sup>2</sup>) Equipment Jumper Factory Terminated on One End</b>					
RGEJ657PFY	57 (1.45)	90°	#6 AWG (16mm <sup>2</sup> ) jumper; bent lug on grounding strip side; provided with .16 oz. (5cc) of antioxidant and two each #12-24 x 1/2", M6 x 12mm, #10-32 x 1/2" and M5 x 12mm thread-forming screws.	1	10

An equal number of M6 x 12mm thread-forming screws also provided in each kit.

\*For use with VBlock preconfigured solutions.