



JKL PART NUMBER	LENGTH A +/- 2mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF4183-20B	183mm	RGB HIGH OUTPUT WHITE 5600° KELVIN	900 @ 0°C	365	5 ± 1	15,000±10%	20,000
BF4220-20B	220mm		1,000 @ 0°C	405	5 ± 1	15,000±10%	20,000
BF4418-20B	418mm		1,400 @ 0°C	765	5 ± 1	15,000±10%	20,000

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0	<b>COMPONENTS CORPORATION</b>			
DRAWN BY <b>L. WENGSTROM</b>		APPVD BY DATE <b>J.K. 9/17/02</b>	SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF 4-20B</b>	
TITLE <b>SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP</b>						
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE <b>NONE</b>	
		9/17/02	RELEASED DATE <b>9/17/02</b>	REVISION DATE	REV. NO.	
					SHEET <b>1 OF 1</b>	