

# CK1,6-ER-1,00BU OIC AG - Crimp contact



1004362

<https://www.phoenixcontact.com/us/products/1004362>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Crimp contact, contact diameter: 1.6 mm, rolled, Socket, contact material: Cu alloy, nickel-plated, contact surface: silver-plated, connection cross section: 0.34 mm<sup>2</sup> ... 1 mm<sup>2</sup>, AWG 22 ... 17

## Commercial data

Item number	1004362
Packing unit	1 pc
Minimum order quantity	100 pc
Sales key	BF65
Product key	BF7AIB
Catalog page	Page 667 (C-2-2019)
GTIN	4055626472546
Weight per piece (including packing)	0.345 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85366990
Country of origin	TR

# CK1,6-ER-1,00BU OIC AG - Crimp contact



1004362

<https://www.phoenixcontact.com/us/products/1004362>

## Technical data

### Notes

General	This product replaces 1884128 CK1,6-ER-0,50BU AG
---------	--

### Mounting

Connection method	Crimp connection
-------------------	------------------

### Product properties

Product type	Crimp contact
Type	Individual female contact
Contact material type	rolled
Series	HC-M-12
	HC-M-EMV
	HC-D
	HC-DD
	VC-D
	HC-M-03/04
	HC-M-17
	HC-K
	HC-Q
	HC-COM
HC-M-42	


### Connection data

Connection method	Crimp connection
Contact connection type	Socket
Connection technology	Crimp connection
Conductor cross section	0.34 mm <sup>2</sup> ... 1 mm <sup>2</sup>
Connection cross section AWG	22 ... 17
Stripping length of the individual wire	4 mm
Conductor cross section flexible	0.34 mm <sup>2</sup> ... 1 mm <sup>2</sup>
Conductor cross section AWG	22 ... 17

### Material specifications

Contact material	Cu alloy, nickel-plated
Contact surface material	silver-plated

### Dimensions

Dimensional drawing	
Length	21 mm

# CK1,6-ER-1,00BU OIC AG - Crimp contact



1004362

<https://www.phoenixcontact.com/us/products/1004362>

## Mechanical characteristics

Contact diameter	1.6 mm
------------------	--------

## Mechanical properties

### Mechanical data

Insertion/withdrawal cycles	≥ 50
-----------------------------	------

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

# CK1,6-ER-1,00BU OIC AG - Crimp contact



1004362

<https://www.phoenixcontact.com/us/products/1004362>

## Classifications

### ECLASS

ECLASS-11.0	27440204
ECLASS-12.0	27440204
ECLASS-13.0	27440204

### ETIM

ETIM 8.0	EC000796
----------	----------

### UNSPSC

UNSPSC 21.0	39121500
-------------	----------

# CK1,6-ER-1,00BU OIC AG - Crimp contact



1004362

<https://www.phoenixcontact.com/us/products/1004362>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)