
Thermofit® Molded Parts Specification Control Drawing Limited Distribution


- 1. All dimensions are in $\frac{\text{Incres}}{[\text{millimeters}]}$
- 2. Dimensions appearing in table are as follows:
 - a As Supplied
 - b After Unrestricted Recovery
- Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.
- 4. Parts shall have cplor stripe .12 wide x 360° around outside surface approx. As shown and must meet requirements set forth in MS-3117 colors shall be as follows:

DASH NO. COLOR

-3 -4 -12

WHITE RED YELLOW





202D2XX-X-61

Boot, Straight, With Lip

Part Number :

Description :

TABLE OF DIMENSIONS													
PART	Н		J			P	R	s	Т	JO	U	нw	JW
NUMBER	Min	Max	Min -3,-4	Min -12	Max	±10%	Ref	Ref	Ref	±10%	±10%	±20%	±20%
	a	b	-3,-4 a	a a	ь	b	b	ь	ь	ь	ь	ь	b
202D211-X-61	.88	<u>.45</u>	.88	<u>.55</u>	<u>.25</u>	4.17	<u>.46</u>	.12	.04	3.40	.47	.06	. <u>045</u>
	[22,4]	[11,4]	[22,4]	[14,0]	[6,4]	[105,9]	[11,7]	[3,0]	1,0]	[86,4]	[11,9]	[1,5]	[1,14]
202D221-X-61	1.01	.59	1.01	.63	.29	4.77	.48	.12	.04	3.88	.47	.06	.045
	[25,7]	[15,0]	[25,7]	[16,0]	[7,4]	[121,2]	[12,2]	[3,0]	[1,0]	[98,6]	[11,9]	[1,5]	[1,14]
202D232-X-61	1.16	.74	1.16	.72	. <u>33</u>	<u>5.46</u>	.48	.12	.04	4.44	.47	.07	. <u>045</u>
	[29,5]	[18,8]	[29,5]	[18,3]	[8,4]	[138,7]	[12,2]	[3,0]	[1,0]	[112,8]	[11,9]	[1,8]	[1,14]
202D242-X-61	1.34	.90	1.34	.84	. <u>38</u>	6.28	.48	.12	.04	<u>5.15</u>	.47	.07	. <u>045</u>
	[34,0]	[22,9]	[34,0]	[21,3]	[9,7]	[159,5]	[12,2]	[3,0]	[1,0]	[130,8]	[11,9]	[1,8]	[1,14]
202D253-X-61	1.47	1.16	1.47	.91	.41	7.00	.55	.12	. <u>065</u>	<u>5.60</u>	.47	.08	. <u>045</u>
	[37,3]	[29,5]	[37,3]	[23,1]	[10,4]	[177,8]	[14,0]	[3,0]	[1,65]	[142,2]	[11,9]	[2,0]	[1,14]
202D263-X-61	1.72	1.34	1.72	1.07	.48	<u>8.00</u>	<u>.60</u>	.12	. <u>065</u>	6.42	.47	.08	. <u>045</u>
	[43,7]	[34,0]	[43,7]	[27,2]	[12,2]	[203,2]	[15,2]	[3,0]	[1,65]	[163,1]	[11.9]	[2,0]	[1,14]
202D274-X-61	1.97	1.62	1.97	1.24	.56	<u>8.00</u>	.60	.12	. <u>065</u>	6.21	.47	.09	. <u>055</u>
	[50,0]	[41,2]	[50,0]	[31,5]	[14,2]	[203,2]	[15,2]	[3,0]	[1,65]	[157,7]	[11,9]	[2,3]	[1,40]
202D285-X-61	2.47	1.85	2.47	1.54	.69	8.00	.63	.12	.08	6.03	.63	.10	. <u>055</u>
	[62,7]	[47,0]	[62,7]	[39,1]	[17,5]	[203,2]	[16,0]	[3,0]	[2.0]	[153,2]	[16,0]	[2.5]	[1,40]
202D296-X-61	2.73	2.35	2.73	1.70	.77	8.00	.63	.12	.08	5.64	.63	.10	. <u>055</u>
	[69,3]	[59,7]	[69,3]	[43,2]	[19,6]	[203,2]	[16,0]	[3,0]	[2,0]	[143,3]	[16,0]	[2,5]	[1,40]
202D299-X-61	3.22	2.64	3.22	2.01	<u>.90</u>	<u>8.00</u>	<u>.63</u>	.12	.08	5.45	<u>.63</u>	.10	. <u>055</u>
	[81,8]	[67,1]	[81,8]	[51,1]	[22,9]	[203,2]	[16,0]	[3,0]	[2,0]	[138,4]	[16,0]	[2,5]	[1,40]

Raychem

-12

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025 (415) 361-6055

Revision: B Date: 4/15/93 Part Number :

202D2XX-X-61

Part Number :

Description: Boot, Straight, With Lip

202D2XX-X-61

Description: Boot, Straight, With Lip


Thermofit Molded Parts Specification Control Drawing Limited Distribution

COMPATABILITY CHART MATERIAL DASH NO. MATERIAL DESCRIPTION RT SPEC COATING DESCRIPTION COATING SLASH NO. COATING S NO. /42 Polyolefin, Semi-rigid RT-301 -3 S-1017 Adhesive Polyolefin, Flexible RT-1304 /42 S-1017 Adhesive

N/A

RT-1312

If this document is printed it becomes uncontrolled. Check for the latest revision.



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE: CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

Raychem

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025 (415) 361-6055

Revision: B Date: 4/15/93 Part Number : 202D2XX-X-61

Description : Boot, Straight, Wiht Lip

CAD FILE MP93100

^{*}VITON, Flexible *VITON is a Registered Trademark of Dupont