



- ⚠ DOUBLE BAR POLARIZATION.
- ⚠ DIMENSION APPLIES AT THE INTERSECTION OF THE POST AND HOUSING.
- ⚠ CENTER POLARIZATION SLOT.
- ⚠ HOUSING: GLASS FILLED NYLON OR PBT, BLACK, UL 94V-0 RATED. POSTS: BRASS.
- ⚠ POSTS: GOLD FLASH OVER PALLADIUM-NICKEL PLATE, 0.38μm[.000015] MIN TOTAL ON THE MATING SURFACES, 2.54μm[.000100] MIN TIN-LEAD PLATE ON THE SOLDER-TAILS, 1.27μm[.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST.
-OR-
0.38μm[.000015] MIN GOLD PLATE ON THE MATING SURFACES, 2.54μm[.000100] MIN TIN-LEAD PLATE ON THE SOLDER-TAILS, 1.27μm[.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST.
- ⚠ DATUMS Y AND Z APPLY IN ZONE I.
- ⚠ NUMBER 1 POSITION INDICATOR.
- ⚠ OPTIONAL AMP IDENTIFICATION NUMBER (DATE CODE). LOCATION APPROXIMATELY WHERE SHOWN.

12	12	50	1-111712-0
ROW T	ROW S	NO OF	PART NUMBER
POST OMITTED		POSITION	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN	M. MORRIS	17JUN98	Tyco Electronics Corporation Harrisburg, PA 17105-3608
DIMENSIONS: mm [INCHES]		CHK	K. FULLER	17JUN98	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	K. FULLER	17JUN98	NAME 108-40018
0 PLC ± -		PRODUCT SPEC			
1 PLC ± -		APPLICATION SPEC			SIZE
2 PLC ± 0.13 [.005]					CAGE CODE
3 PLC ± -					DRAWING NO
4 PLC ± -					RESTRICTED TO
ANGLES ± -		WEIGHT			A1
MATERIAL		CUSTOMER DRAWING		SCALE	4:1
FINISH		SHEET		1	OF 1
		REV			D