1 METER LENGTH





Connector A 132114RP SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 142233 SMB Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector A			Cable		Connector B	
Part #:	132114RP	Part #:	RG-174	Part #:	142233	
Description:	SMA PLUG RP RG316 500	Description:	RG-174 - PE 0.1	Description:	SMB R/A BHD JK RG174 RG316 LMR100	
Type:	SMA	Dielectric:	PE	Description.	50O	
Gender:	Plug	Shielding:	Braid	Type:	SMB	
Body Type:	Straight	Diameter:	0.1	Gender:	Jack	
Contact Type:	Crimp	Impedance:	50 Ohm	Body Type:	Right Angle	
Polarity:	Reverse	Sheathing:	None	Contact Type:	Solder	
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Polarity:	Standard	
Mounting:	Cable	Length:	1 Meter	Impedance:	50 Ohm	
Body Material:	Brass			Mounting:	Bulkhead - Rear Mount	
Body Finish:	Gold			Body Material:	Brass	
IP Rating:	None			Body Finish:	Gold	
Contact Material:	Beryllium Copper			IP Rating:	None	
Contact Finish:	Gold			Contact Material:	Brass	
Max. Freq.:	12.4 GHz			Contact Finish:	Gold	
Booting:	SMA Plug Straight RP			Max. Freq.:	4 GHz	
	3 3 .			Booting:	SMB Jack Right Angle	
				Clocking:	0°	



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-ST-PL-RP/SMB-RA-JK G174 1M

Part No:

Q-6803H0003001M

UNLESS SPECIFIED TOLERANCE:

0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH

IS LESS THAN 12 INCHES