


The LPCXpresso family of boards provides a powerful and flexible development system for NXP's Cortex-M MCUs. The LPCXpresso4337 board has been developed by NXP to enable evaluation of and prototyping with the LPC4300 family of MCUs, and features the LPC4337 in its 100 PIN BGA package option.



Feature summary

The LPCXpresso4337 board includes the following features:

- LPC4337 dual-core (M4F and M0+) MCU running at up to 208MHz
- On-board high-speed USB based debug probe with CMSIS-DAP and LPCXpresso IDE Redlink protocol options, can debug the on-board LPC4337 or external target
- Support for external debug probes
- Tri-color LED
- Target Reset, ISP and WAKE buttons
- Expansion options based on Arduino UNO R3 and Pmod™, plus additional expansion port pins
- On-board 1.8/3.3V or external power supply options
- On-board Ethernet PHY (output available at expansion connectors)
- High speed USB A/B connector for host or slave operation
- 8Mb Macronix quad SPI flash
- UART, I²C and SPI port bridging from LPC4337 target to USB via the on-board debug probe
- FTDI UART connector

LPCXpresso IDE

LPCXpresso IDE supports programming and debugging LPCXpresso boards using the on-board CMSIS-

DAP debug interface, or with an external debug probe such as LPC-Link2. LPCXpresso4337 is ready for use with the LPCXpresso IDE. An external debug probe can be used by simply connecting it to the board via the P1 connector and powering the board via the J3 USB connection.

Partner development tools

The LPCXpresso4337 board can be used with development tools from NXP partners including Atollic, Keil, IAR, Rowley and SEGGER. The board is pre-programmed with CMSIS-DAP firmware, so can also be used with these tool-chains by setting the on-board debug probe to boot from flash (removing the JP3 jumper). Please refer to our partners for details on using their tools with the board.

LPCOpen drivers and examples

LPCOpen software packages allow users to quickly and easily utilize NXP's extensive array of microcontroller software libraries to create and develop multifunctional products. Drivers for the LPCXpresso4337 board can be downloaded for free at <http://www.lpcware.com/lpcopen>.

Board specifications

Recommended operating conditions: 0 to 70°C ambient

Weight: 1.1 ounces

Size: 123 x 59mm (4.8 x 2.3 inches) including connectors

The LPCXpresso4337 board is RoHS compliant.

Please be aware that important notices concerning this document and the product(s) described herein, have been included in the section 'Legal information'.

© NXP B.V. 2015.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 19th January 2015