MATERIAL

lour, matte finish.

**APPLICATIONS** 

STANDARD EXECUTIONS

countersunk head screws.

handwheel or other control devices.

# Housing

for position indicator, technopolymer

Glass-fibre reinforced polyamide based (PA) technopolymer, black co-

- SC.GXX2: three couples of dimples on the bottom of the housing

- SC.GXX5: two holes for supplied M4x14 countersunk head screws.

SC-XX indicator housings are suitable with gravity indicators on any

(to drill according to the type of indicator) and two supplied M4x14

RŏHS

# CP-XX

# Covers

Technopolymer

































### MATERIAL

Polyester based (PBT) technopolymer.

### COLOUR

Light grey, matte finish.


#### MOUNTING

Push-fit. The cover can be removed by using a screwdriver in the proper cavity.

#### **APPLICATIONS**


CP-XX covers are suitable for closing the indicator housing when the indicator is not required.





# METRIC

	Code	Description	△△	Handwheel/indicator combinations
	CE.40002	SC.GXX2	72	GA02 - GA12 - GW12
	CE.40005	SC.GXX5	191	GA05



METRIC

Code	Description	7,7	Handwheels/knobs combinations
CE.40101	CP.X1	6	IZN.60-MBT.60-VHT.85
CE.40102	CP.X2	11 12	ZN.80-MBT.80-VHT.110-VDSC-XX - EWW-X

Position indicators