

	Class 11, manual starter, 14-20 Amps, NEMA 1,
product brand name	Class 11
design of the product	Manual Starter
General technical data	
ambient temperature [°F]	
• during storage	122 ... 176 °F
• during operation	68 ... 140 °F
ambient temperature	
• during storage	50 ... 80 °C
• during operation	20 ... 60 °C
number of poles for main current circuit	3
Contactors	
mechanical service life (operating cycles) of the main contacts typical	100000
Coil	
type of voltage of the control supply voltage	n.a.
Overload relay	
adjustable current response value current of the current-dependent overload release	14 ... 20 A
Mounting/wiring	
fastening method	wall mounting
Short-circuit current rating	
design of the short-circuit trip	magnetic
Certificates/ approvals	
certificate of suitability	UL
Further information	
<p>Industrial Controls - Product Overview (Catalogs, Brochures,...) www.usa.siemens.com/iccatalog</p> <p>Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:11XD3B</p> <p>Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/US/en/ps/US2:11XD3B</p> <p>Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:11XD3B&lang=en</p> <p>Certificates/approvals https://support.industry.siemens.com/cs/US/en/ps/US2:11XD3B/certificate</p>	

last modified:

5/31/2021 