TE Internal #: 638119-1

Housing for Female Terminals, Wire-to-Device / Wire-to-Board, 4 Position, .118 in [3 mm] Centerline, Black, Signal, Cable Mount

(Free-Hanging)

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings











Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 1 mm [.039 in]

Connector System: Wire-to-Board, Wire-to-Device

Number of Positions: 4

Centerline (Pitch): 3 mm [.118 in]

### **Features**

### Product Type Features

Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Board, Wire-to-Device
Sealable	No
Hybrid Connector	No
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	4
Number of Rows	1
Body Features	
Cable Exit Angle	180°
Primary Product Color	Black

А

### **Contact Features**

Connector & Keying Code



Contact Size         1mm           Contact Type         Receptacle           Mating Tab Width         1 mm[.039 in]           Mechanical Attachment         1           I eminal Position Assurance         Yes           Strain Rolled         Without           Mating Alignment Type         Keyed           Mating Alignment         With           Comector Mounting Type         Cable Mount (Free-Hanging)           Housing Features         Housing Material           Housing Material         PA GF           Centerline (Pitch)         3 mm[.118 in]           Dimensions         Comector Height           Comector Height         14.95 mm[.589 in]           Product Length         12.1 mm[.30.75 in]           Usage Conditions         Usage Conditions           Operating Temperature (Max)         70 °C, 75 °C, 80 °C, 80 °C, 90 °C, 100 °C [158 °F][174 °F][174 °F][185 °F][174 °F][174 °F][212 °F]           Operating Temperature Range         -40 – 100 °C[-410 – 212 °F]           Operating Temperature Range         -40 – 100 °C[-410 – 212 °F]           Operating Temperature Range         -40 – 100 °C[-410 – 212 °F]           Operating Temperature Range         -40 – 100 °C[-410 – 212 °F]           Operating Temperature Range         -40 – 100 °C[-410 – 212 °F]		
Machanical Attachment         Yes           Strain Relief         Without           Mating Alignment Type         Keyed           Mating Alignment         With           Connector Mounting Type         Cable Mount (Free-Hanging)           Housing Features         PA GF           Housing Material         PA GF           Centerline (Pitch)         3 mm(.118 in)           Dimensions         Connector Height           Product Width         16 mm(.58 in)           Product Length         1.21 mm(.30.75 in)           Usage Conditions         70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °I] [176 °I] [1	Contact Size	1mm
Mechanical Attachment Terminal Position Assurance Strain Relief Without Mating Alignment Type Keyed Mating Alignment With Connector Mounting Type Cable Mount (Free Hanging) Housing Features Housing Material PA GF Centerline (Pitch) 3 mm.[.118 in]  Dimensions  Connector Height 14.95 mm.[.589 in] Product Width 16 mm.[.63 in] Product Length 1.21 mm.[30.75 in]  Usage Conditions  Operating Temperature (Max) Operating Temperature Range A0 – 100 °C[.40 – 212 °F]  Operation/Application Circuit Application Signal Industry Standards UL Flammability Rating UL P4HB Other Serviceable Yes	Contact Type	Receptacle
Terminal Position Assurance  Strain Relief  Without  Mating Alignment Type  Mating Alignment  Connector Mounting Type  Cable Mount (Free-Hanging)  Housing Features  Housing Material  PA GF  Centerline (Pitch)  3 mm[.118 in]  Dimensions  Connector Height  Product Width  14.95 mm[.589 in]  Product Width  16 mm[.63 in]  Product Length  1.21 mm[30.75 in]  Usage Conditions  Operating Temperature (Max)  Operating Temperature Range  -40 = 100 °C[-40 = 212 °F]  Operation/Application  Circuit Application  Signal  Industry Standards  UL Flammability Rating  UL 94HB  Other  Serviceable  Yes	Mating Tab Width	1 mm[.039 in]
Strain Relief Without  Mating Alignment Type Keyed  Mating Alignment Connector Mounting Type Cable Mount (Free-Hanging)  Housing Features  Housing Material PA GF Centerline (Pitch) 3 mm[.118 in]  Dimensions  Connector Height 14.9s mm[.589 in] Product Width 16 mm[.63 in] Product I ength 1.21 mm[30.75 in]  Usage Conditions  Operating Temperature (Max) 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °F][167 °F][176 °F][185 °F][194 °F][212 °F]  Operating Temperature Range 40 – 100 °C [40 – 212 °F]  Operating Temperature Range UL 94HB  Other  Serviceable Yes	Mechanical Attachment	
Mating Alignment Type Mating Alignment With Connector Mounting Type Cable Mount (Free Hanging)  Housing Features  Housing Material PA GF Centerline (Pitch) 3 mm[.118 in]  Dimensions  Connector Height 14.95 mm[.589 in] Product Width 16 mm[.63 in] Product Length 1.21 mm[30.75 in]  Usage Conditions  Operating Temperature (Max) Operating Temperature Range 40 – 100 °C[ 40 – 212 °F]  Operation/Application  Circuit Application  Industry Standards  UL Flammability Rating UL 94HB  Other  Serviceable Yes	Terminal Position Assurance	Yes
Mating Alignment With  Connector Mounting Type Cable Mount (Free-Hanging)  Housing Features  Housing Material PA GF Centerline (Pitch) 3 mm.[-118 in]  Dimensions  Connector Height 14.95 mm.[-589 in] Product Width 16 mm.[-63 in] Product Length 1.21 mm.[30.75 in]  Usage Conditions  Operating Temperature (Max) 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °F][167 °F][176 °F][185 °F][194 °F][212 °F]  Operating Temperature Range -40 – 100 °C[-40 – 212 °F]  Operating Temperature Signal  Industry Standards  UL Plammability Rating UL 94HB  Other  Serviceable Yes	Strain Relief	Without
Connector Mounting Type  Housing Features  Housing Material PA GF Centerline (Pitch) 3 mm[.118 in]  Dimensions  Connector Height 14.95 mm[.589 in] Product Width 16 mm[.63 in] Product Length 1.21 mm[30.75 in]  Usage Conditions  Operating Temperature (Max) 70 °C, 75 °C, 80 °C, 90 °C, 100 °C [158 °F][167 °F][176 °F][176 °F][194 °F][212 °F]  Operating Temperature Range 40 – 100 °C[-40 – 212 °F]  Operation/Application  Circuit Application  Industry Standards  UL Plammability Rating UL 94HB  Other  Serviceable Yes	Mating Alignment Type	Keyed
Housing Material PA GF Centerline (Pitch) 3 mm[.118 in]  Dimensions  Connector Height 14.95 mm[.589 in] Product Width 16 mm[.63 in] Product Length 1.21 mm[30.75 in]  Usage Conditions  Operating Temperature (Max) 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °F][176 °F][176 °F][185 °F][194 °F][212 °F]  Operating Temperature Range 40 – 100 °C[.40 – 212 °F]  Operating Application Signal  Industry Standards  UL Flammability Rating UL 94HB  Other  Serviceable Yes	Mating Alignment	With
Housing Material PA GF Centerline (Pitch) 3 mm[.118 in]  Dimensions  Connector Height 14.95 mm[.589 in] Product Width 16 mm[.63 in] Product Length 1.21 mm[30.75 in]  Usage Conditions  Operating Temperature (Max) 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °F][167 °F][176 °F][185 °F][194 °F][212 °F]  Operating Temperature Range 40 – 100 °C[-40 – 212 °F]  Operation/Application  Circuit Application Signal  Industry Standards  UL Flammability Rating UL 94HB  Other	Connector Mounting Type	Cable Mount (Free-Hanging)
Centerline (Pitch) 3 mm[.118 in]   Dimensions 14.95 mm[.589 in]   Connector Height 14.95 mm[.589 in]   Product Width 16 mm[.63 in]   Product Length 1.21 mm[30.75 in]   Usage Conditions 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °F][176 °F]	Housing Features	
Dimensions  Connector Height 14.95 mm[.589 in]  Product Width 16 mm[.63 in]  Product Length 1.21 mm[30.75 in]  Usage Conditions  Operating Temperature (Max) 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °F][167 °F][176 °F][176 °F][194 °F][212 °F]  Operating Temperature Range -40 – 100 °C[-40 – 212 °F]  Operation/Application  Circuit Application Signal  Industry Standards  UL Flammability Rating UL 94HB  Other  Serviceable Yes	Housing Material	PA GF
Connector Height 14.95 mm[.589 in]  Product Width 16 mm[.63 in]  Product Length 1.21 mm[30.75 in]  Usage Conditions  Operating Temperature (Max) 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °F][176 °F][176 °F][185 °F][194 °F][212 °F]  Operating Temperature Range 40 – 100 °C[-40 – 212 °F]  Operation/Application Signal  Industry Standards  UL Pahmability Rating UL 94HB  Other  Serviceable Yes	Centerline (Pitch)	3 mm[.118 in]
Product Width 16 mm[.63 in]  Product Length 1.21 mm[30.75 in]  Usage Conditions  Operating Temperature (Max) 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °F][167 °F][176 °F][185 °F][194 °F][212 °F]  Operating Temperature Range -40 – 100 °C[-40 – 212 °F]  Operation/Application  Circuit Application Signal  Industry Standards  UL Flammability Rating UL 94HB  Other  Serviceable Yes	Dimensions	
Product Length 1.21 mm[30.75 in]  Usage Conditions  Operating Temperature (Max) 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °F][167 °F][185 °F][194 °F][212 °F]  Operating Temperature Range -40 – 100 °C[-40 – 212 °F]  Operation/Application  Circuit Application Signal  Industry Standards  UL Flammability Rating UL 94HB  Other  Serviceable Yes	Connector Height	14.95 mm[.589 in]
Usage Conditions  Operating Temperature (Max)  70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °F][176 °F][176 °F][185 °F][194 °F][212 °F]  Operating Temperature Range  -40 – 100 °C[-40 – 212 °F]  Operation/Application  Circuit Application  Signal  Industry Standards  UL Flammability Rating  UL 94HB  Other  Serviceable  Yes	Product Width	16 mm[.63 in]
Operating Temperature (Max)  70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C [158 °F][176 °F][176 °F][185 °F][194 °F][212 °F]  Operating Temperature Range  -40 – 100 °C[-40 – 212 °F]  Operation/Application  Circuit Application  Signal  Industry Standards  UL Flammability Rating  UL 94HB  Other  Serviceable  Yes	Product Length	1.21 mm[30.75 in]
[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F]  Operating Temperature Range -40 – 100 °C[-40 – 212 °F]  Operation/Application  Circuit Application Signal  Industry Standards  UL Flammability Rating UL 94HB  Other  Serviceable Yes	Usage Conditions	
Operation/Application Circuit Application Signal Industry Standards UL Flammability Rating UL 94HB Other Serviceable Yes	Operating Temperature (Max)	[158 °F][167 °F][176 °F][185 °F][194 °F][212 °
Circuit Application  Industry Standards  UL Flammability Rating  Other  Serviceable  Yes	Operating Temperature Range	-40 – 100 °C[-40 – 212 °F]
Industry Standards  UL Flammability Rating  Other  Serviceable  Yes	Operation/Application	
UL Flammability Rating  Other  Serviceable  Yes	Circuit Application	Signal
Other Serviceable Yes	Industry Standards	
Serviceable Yes	UL Flammability Rating	UL 94HB
	Other	
Connector Position Assurance Capable No	Serviceable	Yes
	Connector Position Assurance Capable	No

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

## Compatible Parts







# **Customers Also Bought**















TE Part #2035360-1 1X4 GENERATION Y ASSY KEY A



TE Part #1452421-3 58 POS. CONNECTOR COVER 90 ASSY



TE Part #2840704-1 HOUSING ASSEMBLY, IEC TYPE II

TE Part #9-2177814-1 PIN DIA 3.0, PP

### **Documents**

### **Product Drawings**

4 POSN PLUG ASSY (KEY A)

English

### **CAD Files**

3D PDF

English

**Customer View Model** 

ENG\_CVM\_638119-1\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_638119-1\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_638119-1\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

### **Product Specifications**

**Application Specification** 

English

### **Instruction Sheets**

Category 1 Automotive Plug Connector Assembly

English

Instruction Sheet (U.S.)

English

Housing for Female Terminals, Wire-to-Device / Wire-to-Board, 4 Position, .118 in [3 mm] Centerline, Black, Signal, Cable Mount (Free-Hanging)

