



865 TO 868 MHz RFID PANEL ANTENNA

The Laird PEL86506 antenna is a circularly polarized panel antenna that provides reception and transmission of signals in the 865-868 MHz (Europe Frequency band). Laird industry renowned design methodology achieves maximum efficiency and performance across the entire frequency band. Both VSWR and axial ratios are both excellent and allow the user to achieve the maximum performance for an antenna of this type. This embedded antenna comes with a wide range of connector and cable options.

FEATURES

- Extremely low VSWR and axial ratio
- US band and Europe band available
- Wide range of connector and cable options

MARKETS

- Warehouse
- Distribution center
- Airports and hospitals
- Transit terminals
- Conveyer belt

SPECIFICATIONS

PARAMETER	
Frequency	865 to 868 MHz
Gain	6 dBic
VSWR	1.5:1
Polarization	LH CP
Beamwidth 3dB, Horizontal	100°
Beamwidth 3dB, Elevation	100°
Axial Ration dB	1
Mounting Style	Standoff
Dimensions (mm)	61 x 61 x 4
Connector	Pigtail with Multiple Choices

Americas: +1.847.839.6925
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com


www.lairdtech.com

Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective by reason of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.




PATTERNS

865 MHz




Linear A

867.5 MHz




Linear A


865 MHz




Linear A



Linear B



Linear B



Linear B

PART NUMBERS

Part Number	Specifications
PEL86506-61RTN	865-868 MHz panel, RHCP, 6 dBic, EMBD, 61 cm, RTNM
PEL86506-61SMAM	865-868 MHz panel, RHCP, 6 dBic, EMBD, 61 cm, SMAM

ANT-DS-PEL86506 1115

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.