

Ratings

Voltage: 300 V
 Temperature: -25 to 80 °C
 Flammability: VW-1

Conductor

Conductor count: 10
 Gauge: 20 AWG 0.52 mm²
 Material: tinned copper strands
 Strand size: ϕ 0.16 mm x 26
 Resistance at 20 °C: 36.7 Ω /km max

Insulator

Material: PVC
 Color: red, black, white, yellow, blue, green, orange, purple, gray, brown
 Diameter: ϕ 1.55 \pm 0.10 mm
 Nominal thickness: 0.28 mm
 Resistance at 20 °C: 10 M Ω /km min



Outer jacket

Material: PVC
 Color: white
 Diameter: ϕ 7.8 \pm 0.30 mm
 Nominal thickness: 0.8 mm

Wire marking: E339579 UL AWM STYLE 2464 20 AWG 80°C 300V VW-1 --- cUL AWM I/II A 80°C 300V FT1 TENSILITY

Tests

Insulation tensile strength: 2.11 kgf/mm²
 Jacket tensile strength: 1.05 kgf/mm²
 After aging at 113 \pm 2 °C for 7 days:
 Minimum tensile strength 70 % original
 Minimum elongation 65 % original
 Heat shock: 121 \pm 1 °C /1 hour, no observed degradation
 Deformation: 121 \pm 1 °C /1 hour, \leq 50 %
 Cold bend: -10 \pm 2 °C /1 hour, no observed cracking



Revision:	Date:	Description:	Prepared: AW <small>Digitally signed by AW Date: 2019.05.16 15:43:02 -07'00'</small>	Notes:	<h1>TENSILITY</h1> <small>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</small>
A	5/16/2019	Initial release	Verified: JP <small>Digitally signed by JP Date: 2019.05.17 14:29:19 -07'00'</small>	RoHS compliant	
			Dimensions are in millimeters. Tolerances: X: \pm 0.5 mm X.X: \pm 0.3 mm X.XX: \pm 0.05 mm	Function test: no open, no short circuit, no intermittent	
				Description: Wire, 10C TS, 20 AWG, UL2464, 300V, 80C, 7.8 mm, VW-1, PVC, 60P, white	
				Size: A	Part number: 30-01338
				Scale: 8:1	Sheet 1 of 1

5

4

3

2

1