RAST

TE Internal #: 2-284865-3

Standard Edge Connectors, Wire-to-Board, 3 Position, .098 in [2.5 mm] Centerline, Insulation Displacement (IDC), 1 Row, Red, PBT

GF, Fully Loaded

View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > Standard Edge Connectors





Connector System: Wire-to-Board

Number of Positions: 3

Centerline (Pitch): 2.5 mm [.098 in]

Termination Method to Wire & Cable: Insulation Displacement (IDC)

Number of Rows: 1

Features

Product Type Features

| Connector System | Wire-to-Board |
|-----------------------------------|-----------------------|
| Connector & Housing Type | Receptacle |
| Connector & Contact Terminates To | Printed Circuit Board |
| Configuration Features | |

| Number of Insulation Displacement Slots 3 |
|---|
| |
| Compatible With Wire & Cable Type Discrete Wire |
| Number of Positions 3 |
| Number of Rows 1 |
| Connector Contact Load Condition Fully Loaded |
| PCB Mount Orientation Right Angle |

Electrical Characteristics

| Operating Voltage | 63 VAC | |
|-------------------|--------|--|

Body Features



| Keying Between Cavity Locations | 1&2 |
|---|-------------------------------|
| Primary Product Color | Red |
| Contact Features | |
| Contact Retention Within Housing | Without |
| PCB Contact Termination Area Plating Material Thickness | 4 – 10 μm |
| Contact Type | Socket |
| Contact Mating Area Plating Material | Tin |
| Contact Base Material | Phosphor Bronze |
| Contact Current Rating (Max) | 2 A |
| Termination Features | |
| Termination Method to Wire & Cable | Insulation Displacement (IDC) |
| Mechanical Attachment | |
| Mating Alignment Type | Keyed |
| Mating Retention | With |
| Mating Alignment | With |
| PCB Mount Alignment | With |
| PCB Mount Retention | With |
| Connector Mounting Type | Board Mount |
| Housing Features | |
| Housing Entry Configuration | Both Ends Closed |
| Centerline (Pitch) | 2.5 mm[.098 in] |
| Housing Material | PBT GF |
| Dimensions | |
| Card Slot Depth | 5 mm[.2 in] |
| Connector Height | 7.35 mm[.29 in] |
| PCB Thickness (Recommended) | 1.5 mm[.059 in] |
| Compatible Insulation Diameter Range | 1.3 – 2.1 mm[.05 – .08 in] |
| Wire Size | .22 – .35 mm² |
| Usage Conditions | |
| Operating Temperature Range | -40 - 110 °C[-40 - 230 °F] |
| Operation/Application | |
| Circuit Application | Signal |



Packaging Features

| Packaging Quantity | 448 |
|--------------------|------|
| Packaging Method | Tray |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts





Customers Also Bought






TE Part #284930-5
DUOPLUG Standard, female conn.



TE Part #1-282004-1 AMP MONO-SHAPE TAB CONN 4P. G



TE Part #3-284932-3 DUOPLUG MKI STD, KEYED 2/3, 3 POS., RED



TE Part #2-284932-4 DUOPLUG MKI STD,KEYED 3/4,4 POS, BLACK



TE Part #1-282002-3 AMP MONO-SHAPE TAB CONN 2P. G



TE Part #1-282044-1 AMP MONO-SHAPE P.C.B.CONN4P. G



TE Part #1-282086-7 AMP MONO-SHAPE CONN.SINGLE WAY LP



TE Part #1-284396-1 AMP MONO-SHAPE 3 POS TAB CONN



TE Part #284930-4
DUOPLUG Standard, female conn.



TE Part #4-284932-5 DUOPLUG MKI STD,KEYED 2/3,5 POS, ORANGE

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-284865-3_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-284865-3_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-284865-3_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Product Specifications

Application Specification

English

Product Environmental Compliance

Standard Edge Connectors, Wire-to-Board, 3 Position, .098 in [2.5 mm] Centerline, Insulation Displacement (IDC), 1 Row, Red, PBT GF, Fully Loaded



MD_2-284865-3_06052018120_dmtec

English

MD_2-284865-3_06052018120_dmtec

English

Agency Approvals

Agency Approval Document

English