PRODUCT DATASHEET

NiMH Battery Charger (CHFM)

Asia Pacific Region Download Instructions

SAFE

• Safety on/off switch



EASY

• Convenient displays tell when charge is complete



ECONOMI CAL

 Batteries can be charged hundreds of times



Before Using Your Charger: Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Easy Charger

safe

smart battery charg status sleek

Product Detail:

Designation: Easy Charger - Asia Pacific Region

Color: Gun Metal Gray with Pearl Face Plate

Charge Capability: "AA" (2) or (4)

"AAA" (2) or (4)

"AA" (2) and "AAA" (2) Simultaneously

Charging Time: (estimate)

:	Battery	Capacity	Estimated
(!	(NiMH)	(mAh)	(time)
	AA	2650	9.0 hrs
	AA	2500	8.5 hrs
	AA	2000	7.0 hrs
	AAA	1000	10.0 hrs
	AAA	900	9.0 hrs
	AAA	700	7.0 hrs

Shutoff Mechanism: Delta V Detection

Timer (10 hours \pm 30 minutes) Temperature detection at 55°C

Charging Current: AA @ DC 2.8V, $360mA \pm 10\%$

AAA @ DC 2.8V, 120mA ± 10%

Trickle Charge: None

Input Rating: Universal Voltage: 100-240vac, 50/60Hz Input Current: Maximum 150mA at AC 120V/60Hz

Input Power: ≤ 6W

Typical Weight: 166.5 grams (5.9 oz.)
Dimensions (mm): 133 x 89 x 32 (H x L x W)

Rev Polarity Protection: Yes Primary Battery Detection: Yes

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication.

© Energizer

Contents herein do not constitute a warranty.

