

RA-200

GRAY

Ø0.25

1.21

22 AWG, UL STYLE 1354 80° 30V
PVC INSULATED
Ø0.155 REF
GRAY CABLE

"L"
CABLE
LENGTH

1.88 REF

1.50 REF

0.38
REF

STRIP & TIN

1.50 REF

15

A

84

X

RoHS COMPLIANT

2ND END - STRIP & TIN

CABLE LENGTH
N - 10 FEET ± 1.00 INCH

TYPE OF CABLE - W-1000

1ST END - RA-200

CUSTOMER DRAWING

WIRING	
TIP	CENTER CONDUCTOR
SLEEVE	SHIELD

NOTES:

1. MATERIALS:
OVERMOLD - THERMOPLASTIC
PLUG - COPPER ALLOY, NICKEL PLATED
2. THIS PRODUCT IS RoHS COMPLIANT.

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES
- TWO PLACE DECIMALS ±0.02
- THREE PLACE DECIMALS ±0.005

SIZE *	WIDTH *	MULT *	LBS/M *	TEMPER *
FINISH *			MATERIAL *	
SPEC No. *			SPEC No. *	
FIRST USED ON *		SCALE 1:1		
DATE DRAWN	BY	CHKD	APVD	
12-11-09	JEB	JEB	TJK	
		12-11-09	01-13-10	
NAME			PART No.	REV
CABLE ASSEMBLY RA-200 TO S & T, RoHS			15A_84X	A
SHEET 1			OF 1	

REV	ECO NUMBER	DATE	BY	APVD
A	26206	01-29-07	JEB	TJK
REVISIONS				

DO NOT SCALE DRAWING

SolidWorks CAD File

