


RECOMMEND P.C.B. LAYOUT



CIRCUIT: SPST

CONTACT CONFIGURATION

- NOTES:
1. ALL DIMENSIONS IN MM
  2. GENERAL TOLERANCE: 0.0=±0.4  
0.00=±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. ACTUATION FORCE: 130±40gf
  5. TRAVEL TO MAKE: 0.3mm +0.4/-0.0
  6. RATING: 30ma, @12V DC
  7. CONTACT RESISTANCE: 50 milliohms typical
  8. DIELECTRIC STRENGTH: 300V RMS min at sea level.
  9. ELECTRICAL LIFE CYCLE: 1,000,000 make & break cycles at full load.
- ▲10. DESIGNATE MAJOR DIMENSIONS

**E-SWITCH®**

REV.	ECN No.	DESCRIPTION	DATE	CHKD
B	10088	REVISED & REDRAWN	1/27/99	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED				

TITLE	SCALE	DATE	DR	DWG	REV
GS 10.00 F130 QP - Washable Tact Switch	5:1	1/13/99	MM	L600001	B