



**Ball Joint 360
Rotation**



Mighty Cam ES	Macro Lens	Ultimate Flexibility	LED Ring Light
HDMI/USB Camera designed for quick & accurate inspection	7x - 70x Magnification at a 6" working distance	18" Flexible arm with a 360 ball joint	Provides uniformity & shadow free illumination



Excellent Color Reproduction



**USB Mode- Advanced Imaging/
Measurement Software Included**



**HDMI Mode: Image/Video Capture,
On-Screen Tools (No PC required)**

Mighty Cam ES

[7x-70x] w/ Macro Lens & Flex-Arm Stand

High Definition 1080p inspection system with a 22" monitor offering superb image quality. **Provides a magnification range of 7x to 70x with a 6" working distance.** You can operate this system with or without a PC. Without a PC, the camera connects directly to the included HDMI monitor. View and record images using the included on screen tools. Images & videos can be saved to the included SD card. Connect the camera to a PC to utilize more advanced features in the included software. The included LED ring light allows you to illuminate the object to get the sharpest and greatest detail.

Features

- Superior optics: 7x-70x magnification at a 6 inch working distance
- Camera features HDMI and USB outputs for use with an HD monitor or PC
- Save high resolution image/video files to the included SD Card no PC required
- Advanced imaging/measurement software included for PC mode
- 18 inch flexible arm with a 360 ball joint provides limitless positioning options
- LED ring light with 96 ultra-bright, adjustable LEDs

Mighty Cam ES		
<i>7x-70x w/ Macro Lens & Flex-Arm Stand</i>		
Item #	26700-121-ES	
Magnification	7x - 70x	
Working Distance	6"	
Interface	USB 2.0 & HDMI	
Resolution	2MP 2592 (H) x 1944 (V)	
Frame Rate	USB 2.0 @ 15FPS	HDMI @ 15FPS
Software	USB 2.0 Mosaic V2	HDMI Cloud 1.0 ver
Package Contents	<ul style="list-style-type: none"> • Mighty Cam ES (26100-259) • Computar Macro Lens (26700-181) • FlexArm With Table Clamp (26800B-557) • 360 Ball Joint (26700-412) • LED Ring Light (26200B-216) • 22" LCD HD Monitor (26700-406) 	